

Version 2

Reviewed on 09/14/2016

1 Identification

- · Product identifier
- · Product Description: Epoxy curing agent
- · Product code: Cardolite LITE 2401
- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Cardolite Corporation 11 Deer Park Drive, Suite 124 Monmouth Junction, NJ 08852 USA Tel: (973) 344-5015 Regulatory@cardolite.com
- · Information department: Product safety department
- Emergency telephone number: 24 Hour Emergency: 800-424-9300 CHEMTREC

2 Hazard(s) identification

· Classification of the substance or mixture

GHS05 Corrosion

- Skin Corr. 1B H314 Causes severe skin burns and eye damage.
- Eye Dam. 1 H318 Causes serious eye damage.



Acute Tox. 4 H302 Harmful if swallowed.Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Danger

- Hazard-determining components of labeling: 3-aminomethyl-3,5,5-trimethylcyclohexylamine m-phenylenebis(methylamine) 3,6,9-triazaundecamethylenediamine
 Hazard statements
- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.

(Contd. on page 2)

US



Version 2

Reviewed on 09/14/2016

Product Description: Epoxy curing agent

.	(Contd. of page 1)
· Precautionary	
P260	Do not breathe dusts or mists.
P303+P361+P	353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
 Classification NFPA ratings 	system:
F	lealth = 3 ire = 1 leactivity = 0
· HMIS-ratings	(scale 0 - 4)
FIRE 1	Health = 3 Fire = 1 Reactivity = 0
· Other hazards	
••••••	7 T and vPvB assessment
• PBT: Not appli	
· vPvB: Not app	
VI VD. Not app	
3 Compositio	on/information on ingredients
	racterization: Mixtures /lixture of the substances listed below with nonhazardous additions.
· Dangerous co	
Bungorous ou	in parion ta

•	a componenta.	
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	35 - 55.0%
	Skin Corr. 1B, H314; (1) Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	
1477-55-0	m-phenylenebis(methylamine)	5.0 -12.0%
	Skin Corr. 1B, H314; (1) Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1B, H317	
112-57-2	3,6,9-triazaundecamethylenediamine	1.0 - 2.5%
	Skin Corr. 1B, H314; (1) Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

(Contd. on page 3)

US



Version 2

Reviewed on 09/14/2016

Product Description: Epoxy curing agent

(Contd. of page 2)

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Immediately call a doctor.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters Promptly isolate the scene by removing all person from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent. Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
 Reference to other sections
 See Section 7 for information on onto head headling.

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- Precautions for safe handling
 Ensure good ventilation/exhaustion at the workplace.
 Prevent formation of aerosols.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.

(Contd. on page 4)

US

(Contd. of page 3)



Safety Data Sheet acc. to OSHA HCS

Version 2

Reviewed on 09/14/2016

Product Description: Epoxy curing agent

• Further information about storage conditions: Keep receptacle tightly sealed.

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

112-57-2 3,6,9-triazaundecamethylenediamine

WEEL Long-term value: 5 mg/m³

Skin; DSEN

· Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

(Contd. on page 5)

119



Version 2

Reviewed on 09/14/2016

Product Description: Epoxy curing agent

(Contd. of page 4)

 Information on basic physical and General Information 	chemical properties
 Appearance: Form: Color: Odor: Odor threshold: 	Liquid Light yellow Amine-like Not determined.
· pH-value:	Not determined.
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. Undetermined.
· Flash point:	> 110 °C (> 230 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
 Explosion limits: Lower: Upper: 	Not determined. Not determined.
· Vapor pressure:	Not determined.
 Density at 25 °C (77 °F): Relative density Vapor density Evaporation rate 	0.95262 g/cm ³ (7.95 lbs/gal) Not determined. Not determined. Not determined.
 Solubility in / Miscibility with Water: 	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wat	er): Not determined.
^{··} Viscosity: Dynamic at 25 ℃ (77 ℉): Kinematic:	~ 90 cps Not determined.
· Solvent content:	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 6)



Version 2

Reviewed on 09/14/2016

Product Description: Epoxy curing agent

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects

- · Acute toxicity:
- LD/LC50 values that are relevant for classification: Irritating to eyes and skin.

1477-55-0 m-phenylenebis(methylamine)

Oral LD50 1040 mg/kg (rat)

Inhalative LC50/4 h 2.4 mg/l (rat)

112-57-2 3,6,9-triazaundecamethylenediamine

Dermal LD50 660 mg/kg (rabbit)

· Primary irritant effect:

- on the skin: Caustic effect on skin and mucous membranes.
- on the eye: Strong caustic effect.
- · Sensitization: Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

- Harmful
- Corrosive Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)


None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:
- Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 7)



Cardolite

(Contd. of page 5)

(Contd. of page 6)



Safety Data Sheet acc. to OSHA HCS

Version 2

Reviewed on 09/14/2016

Product Description: Epoxy curing agent

Must not reach bodies of water or drainage ditch undiluted or unneutralized. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

· Results of PBT and vPvB assessment

- · PBT: Not applicable.
- vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

· UN-Number · DOT, ADR, IMDG, IATA	UN2735
 UN proper shipping name DOT 	Amines, liquid, corrosive, n.o.s. (n
· ADR	phenylenebis(methylamine), Isophoronediamine) 2735 Amines, liquid, corrosive, n.o.s. (n phenylenebis(methylamine), Isophoronediamine)
· IMDG, IATA	AMINES, LIQUID, CORROSIVE, N.O.S. (n phenylenebis(methylamine), ISOPHORONEDIAMINE)
 Transport hazard class(es) 	
· DOT	
· Class · Label	8 Corrosive substances 8
· ADR	
· Class	8 Corrosive substances Miscellaneous dangerous substances and articles



Version 2

Reviewed on 09/14/2016

Product Description: Epoxy curing agent

	(Contd. of page
· Label	8
· IMDG, IATA	
· Class · Label	8 Corrosive substances 8
 Packing group DOT, ADR, IMDG, IATA 	III
 Environmental hazards: Marine pollutant: 	No
 Special precautions for user Danger code (Kemler): EMS Number: Segregation groups 	Warning: Corrosive substances 80 F-A,S-B Alkalis
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
· Transport/Additional information:	
 DOT Quantity limitations 	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
 ADR Excepted quantities (EQ) 	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN2735, Amines, liquid, corrosive, n.o.s. (m phenylenebis(methylamine), lsophoronediamine), 8, III

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

(Contd. on page 9)

US



Version 2

Reviewed on 09/14/2016

Product Description: Epoxy curing agent

Chemicals know	vn to cause cancer:
None of the ingre	edients is listed.
Chemicals know	vn to cause reproductive toxicity for females:
None of the ingre	
Chemicals know	vn to cause reproductive toxicity for males:
None of the ingre	
v	vn to cause developmental toxicity:
None of the ingre	
Carcinogenic ca	ental Protection Agency)
None of the ingre	
v	
•	Limit Value established by ACGIH)
None of the ingre	
•	onal Institute for Occupational Safety and Health)
None of the ingre	
The product is cla Hazard pictogra	assified and labeled according to the Globally Harmonized System (GHS).
The product is cla	assified and labeled according to the Globally Harmonized System (GHS).
Hazard pictogra	assified and labeled according to the Globally Harmonized System (GHS).
The product is cla Hazard pictogra GHS05 GHS07 Signal word Dar Hazard-determin	assified and labeled according to the Globally Harmonized System (GHS).
The product is cla Hazard pictogra GHS05 GHS07 Signal word Dar Hazard-determin 3-aminomethyl-3	assified and labeled according to the Globally Harmonized System (GHS). ms 7 nger ning components of labeling: ,5,5-trimethylcyclohexylamine
The product is cla Hazard pictogra GHS05 GHS07 Signal word Dar Hazard-determin 3-aminomethyl-3 m-phenylenebis(i	assified and labeled according to the Globally Harmonized System (GHS). ms 7 nger ning components of labeling: ,5,5-trimethylcyclohexylamine methylamine)
The product is cla Hazard pictogra GHS05 GHS07 Signal word Dar Hazard-determin 3-aminomethyl-3 m-phenylenebis(1 3,6,9-triazaunded Hazard stateme	assified and labeled according to the Globally Harmonized System (GHS).
The product is cla Hazard pictogra GHS05 GHS07 Signal word Dar Hazard-determin 3-aminomethyl-3 m-phenylenebis(1 3,6,9-triazaunded Hazard statemen H302 Harmful if s	assified and labeled according to the Globally Harmonized System (GHS). T T T T T T T T T T T T T
The product is cla Hazard pictogra GHS05 GHS07 Signal word Dar Hazard-determin 3-aminomethyl-3 m-phenylenebis(1 3,6,9-triazaunded Hazard statemen H302 Harmful if s H314 Causes ser	assified and labeled according to the Globally Harmonized System (GHS).
The product is cla Hazard pictogra GHS05 GHS07 Signal word Dar Hazard-determin 3-aminomethyl-3 m-phenylenebis(i 3,6,9-triazaundec Hazard statemen H302 Harmful if si H314 Causes ser H317 May cause	assified and labeled according to the Globally Harmonized System (GHS).
The product is cla Hazard pictogra GHS05 GHS07 Signal word Dar Hazard-determin 3-aminomethyl-3 m-phenylenebis(i 3,6,9-triazaundec Hazard statemen H302 Harmful if si H314 Causes ser	assified and labeled according to the Globally Harmonized System (GHS).
The product is cla Hazard pictogra GHS05 GHS07 Signal word Dar Hazard-determin 3-aminomethyl-3 m-phenylenebis(i 3,6,9-triazaundeo Hazard statemen H302 Harmful if s H314 Causes se H317 May cause Precautionary s P260	assified and labeled according to the Globally Harmonized System (GHS). ms 7 nger ning components of labeling: ,5,5-trimethylcyclohexylamine methylamine) camethylenediamine nts swallowed. vere skin burns and eye damage. an allergic skin reaction. tatements Do not breathe dusts or mists.
The product is cla Hazard pictogra GHS05 GHS07 Signal word Dar Hazard-determin 3-aminomethyl-3 m-phenylenebis(n 3,6,9-triazaundeo Hazard statemen H302 Harmful if s H314 Causes ser H317 May cause Precautionary s P260 P303+P361+P35 P305+P351+P33	assified and labeled according to the Globally Harmonized System (GHS). The second state of the second st
The product is cla Hazard pictogra GHS05 GHS07 Signal word Dar Hazard-determin 3-aminomethyl-3 m-phenylenebis(n 3,6,9-triazaundeo Hazard statemen H302 Harmful if s H314 Causes ser H317 May cause Precautionary s P260 P303+P361+P35 P305+P351+P33 P310	assified and labeled according to the Globally Harmonized System (GHS). The second state of the System (GHS). The second state of the second state o
The product is cla Hazard pictogra GHS05 GHS07 Signal word Dar Hazard-determin 3-aminomethyl-3 m-phenylenebis(r 3,6,9-triazaundec Hazard statemethyl-3 Magnetic ser H314 Causes ser H314 Causes ser H317 May cause Precautionary s P260 P303+P361+P35 P305+P351+P33 P310 P405	assified and labeled according to the Globally Harmonized System (GHS). The second state of the System (GHS). The second state of
The product is cla Hazard pictogra GHS05 GHS07 Signal word Dar Hazard-determin 3-aminomethyl-3 m-phenylenebis(n 3,6,9-triazaundeo Hazard statemen H302 Harmful if s H314 Causes ser H317 May cause Precautionary s P260 P303+P361+P35 P305+P351+P33 P310	assified and labeled according to the Globally Harmonized System (GHS). The second state of the System (GHS). The second state of the second state o



Version 2

Reviewed on 09/14/2016

Product Description: Epoxy curing agent

(Contd. of page 9)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: Mr Eleazar dela Cruz
- Date of preparation / last revision 09/14/2016 / 1

 Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TVL: Treshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1B: Skin sensitisation - Category 1B US