Cardolite® NT-1541I73 Epoxy Curing Agent Preliminary Technical Datasheet

DESCRIPTION

Cardolite NT-1541I73 is an epoxy curing agent based on reactive polyamide technology.

TYPICAL PROPERTIES

Property	Typical Values	Test Method
Appearance	Yellow liquid	Visual
Color (Gardner)	≤10	ASTM D1544
Viscosity @ 25°C (cPs)	1,000 - 3,500	ASTM D2196
Amine Value (mg KOH/g)	145 - 185	ASTM D2074
Theoretical Active Hydrogen Equivalent (AHEW) ¹	271.5	Calculated
Solids (% weight)	71 - 75	ASTM D2369-98
Density @ 25°C (kg/L) (lbs/gal)	0.915 7.64	ASTM D1475
Flash point	21.1°C / 70°F	ASTM D93
Recommended Use Level (phr, EEW 190 / 666.7)	142.9 / 40.7	
Shelf Life (Months)	24	

Typical properties are not to be construed as specifications

CURE PROPERTIES

	FORMULATION	TEST METHOD
Liquid Epoxy Resin (pbw, EEW 190)	100	
Cardolite NT-1541I73 (pbw)	142.9	
Gel time, 50 g @ 25°C (min)	453	NTM-15

¹Based on total product weight

REGULATORY STATUS

Please refer to the material safety data sheet (MSDS). Specific information regarding chemical inventory listing can be obtained from your local sales representative.

SAFETY PRECAUTIONS

Please refer to the material safety data sheet (MSDS). Copies of the MSDS can be requested on the Cardolite website or via your local sales representative.

STABILITY AND STORAGE

Cardolite products may absorb moisture and carbon dioxide when left in open containers, which could result in increased viscosity, discoloration, reduction of reactivity, and/or crystallization of the products. These products should be kept tightly sealed in their original containers when not in use, and stored in a cool, dry place.

CONTACT INFORMATION



http://www.cardolite.com

Cardolite Corporation 11 Deer Park Drive STE 124 Monmouth Junction, NJ 08852 United States of America

T: +1-973-344-5015

Cardolite Specialty Chemicals Europe NV Wijmenstraat 21K / 2 B-9030 Mariakerke (Gent) Belgium

T: +32 (0) 92658826

Cardolite Specialty Chemicals India LLP Plot No. IP-1 & IP-2, Mangalore Special Economic Zone Bajpe, Mangalore 574 142, India

T: + 91 (0) 824 2888 300

Cardolite Chemical Zhuhai Ltd. Biyang Road Harbor Industrial Zone Zhuhai, Guangdong 519050 P.R. China

T: +86-756-726-9066

DISCLAIMER & COPYRIGHT

All statements, technical information and recommendations contained herein are based on tests Cardolite believes to be reliable, but the accuracy or completeness thereof is not guaranteed. Actual test method procedures may differ from listed standards; major differences are noted. Limitation of liability and remedy: Purchase or use of these products constitutes an agreement with seller and manufacturer that, if the product proves to be defective or unsuitable, seller's and manufacturer's liability and the exclusive remedy, regardless of tort or contract theory or of incidental or consequential damages shall be to receive, at seller's or manufacturer's option, an equivalent quantity of replacement product or a refund of the purchase price. This datasheet is copyrighted to Cardolite Corporation and may be reproduced but not altered in any way.

Cardolite Preliminary Technical Datasheet NT-1541I73

Issue Date: 11/2016

Copyright © 2007-2016 Cardolite Corporation