

Version number 1 Revision: 11.04.2016

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Epoxy curing agent
- · Article number: Cardolite FormuLITE 2401B
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- Product category PC9a Coatings and paints, thinners, paint removers
- · Application of the substance / the mixture Coating
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

CARDOLITE SPECIALTY CHEMICALS EUROPE N.V.

Wijmenstraat 21 K, Bus 2 9030 Mariakerke – Gent

Tel.: +32 9 265.88.26 (Belgium) Fax.: +32 9 265.88.24 (Belgium) regulatory@cardolite.com eumsds@cardolite.com

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: During business hours: +32 9 265.88.26 (Belgium)

### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

3-aminomethyl-3,5,5-trimethylcyclohexylamine



Version number 1 Revision: 11.04.2016

Trade name: Epoxy curing agent

(Contd. of page 1)

m-phenylenebis(methylamine)

3,6,9-triazaundecamethylenediamine

· Hazard statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 2855-13-2 EINECS: 220-666-8 Index number: 612-067-00-9	3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	25,0 - 55,0%
CAS: 1477-55-0 EINECS: 216-032-5	m-phenylenebis(methylamine) Skin Corr. 1B, H314;  Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412	5,0 - 12,0%
CAS: 112-57-2 EINECS: 203-986-2 Index number: 612-060-00-0	3,6,9-triazaundecamethylenediamine  Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	1,0 - 2,5%

<sup>·</sup> Additional information: For the wording of the listed risk phrases refer to section 16.

### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)



Version number 1 Revision: 11.04.2016

Trade name: Epoxy curing agent

(Contd. of page 2)

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters

Promptly isolate the scene by removing all person from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

· Protective equipment: Mouth respiratory protective device.

### **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed and in a well ventilated place.

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Cardolite epoxy resins and hardeners may absorb moisture and carbon dioxide when left in open containers, which could result in increased viscosity, discoloration, reduction of reactivity, and/or

(Contd. on page 4)



Version number 1 Revision: 11.04.2016

Trade name: Epoxy curing agent

(Contd. of page 3)

crystallization of the products. These products should be kept tightly sealed in their original containers when not in use, and stored in a cool, dry place. Some Cardolite epoxy resins might crystallize. This reversible, physical phenomena can be greatly avoided by storing the resin at temperatures above 25 °C.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 5)



Not determined.

ng date 11.04.2016 Version number 1 Revision: 11.04.2016

Trade name: Epoxy curing agent

· Body protection: Protective work clothing

(Contd. of page 4)

#### **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

· pH-value:

Form: Liquid
Colour: Light yellow
Odour: Amine-like
Odour threshold: Not determined.

· Change in condition

Melting point/Melting range: Undetermined. Boiling point/Boiling range: Undetermined.

• Flash point:  $> 110 \, ^{\circ}$ C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature:

**Decomposition temperature:** Not determined.

• **Self-igniting:** Product is not selfigniting.

• **Danger of explosion:** Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined. Upper: Not determined.

· Vapour pressure: Not determined.

Density at 25 °C: 0.95262 g/cm³
 Relative density Not determined.
 Vapour density Not determined.
 Evaporation rate Not determined.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

**Dynamic at 25 °C:** ~ 90 cps **Kinematic:** Not determined.

· Solvent content:

Solids content: 99.0 %

• **9.2 Other information** No further relevant information available.

### **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability Product is stable.

(Contd. on page 6)

(Contd. of page 5)



# Safety data sheet according to 1907/2006/EC, Article 31

Version number 1 Revision: 11.04.2016

Trade name: Epoxy curing agent

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- Acute toxicity

Harmful if swallowed.

· LD/LC50 values relevant for classification:

Irritating to eyes and skin.

#### 1477-55-0 m-phenylenebis(methylamine)

Oral LD50 1040 mg/kg (rat) Inhalative LC50/4 h 2,4 mg/l (rat)

### 112-57-2 3,6,9-triazaundecamethylenediamine

Dermal LD50 660 mg/kg (rabbit)

- · Primary irritant effect:
- Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

(Contd. on page 7)

(Contd. of page 6)



### Safety data sheet according to 1907/2006/EC, Article 31

Version number 1 Revision: 11.04.2016

Trade name: Epoxy curing agent

· 12.5 Results of PBT and vPvB assessment

- · **PBT:** Not applicable. · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

·		
14.1 UN-Number ADR, IMDG, IATA	UN2735	
14.2 UN proper shipping name ADR	2735 AMINES, LIQUID, CORROSIVE, N.O.S. (r phenylenebis (methylamine) ISOPHORONEDIAMINE)	
·IMDG	AMINES, LIQUID, CORROSIVE, N.O.S. (nphenylenebis (methylamine) ISOPHORONEDIAMINE)	
IATA	Amines, liquid, corrosive, n.o.s. (n phenylenebis(methylamine), Isophoronediamine)	
14.3 Transport hazard class(es)		
ADR		
Class	8 Corrosive substances. Miscellaneous dangerous substances and articles.	
Label	8	
· IMDG, IATA		
Class Label	8 Corrosive substances.	
· 14.4 Packing group · ADR, IMDG, IATA	III	
14.5 Environmental hazards: Marine pollutant:	No	

(Contd. of page 7)

# Cardolite Printing date 11.04.2016

# Safety data sheet according to 1907/2006/EC, Article 31

Version number 1 Revision: 11.04.2016

Trade name: Epoxy curing agent

• 14.6 Special precautions for user Warning: Corrosive substances.

• 14.6 Special precautions for user Warning: Corrosive substances
• Danger code (Kemler): 80

• EMS Number: F-A,S-B
• Segregation groups Alkalis
• Stowage Category A

• Segregation Code SG35 Stow "separated from" acids.

· 14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)Excepted quantities (EQ)5LCode: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· Transport category 3
· Tunnel restriction code E

·IMDG

Limited quantities (LQ)Excepted quantities (EQ)Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml
 UN "Model Regulation":
 UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S.

UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (M-PHENYLENEBIS (METHYLAMINE),

ISOPHORONEDIAMINE), 8, III

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

3-aminomethyl-3,5,5-trimethylcyclohexylamine m-phenylenebis(methylamine)

3.6.9-triazaundecamethylenediamine

· Hazard statements

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 9)



nting date 11.04.2016 Version number 1 Revision: 11.04.2016

Trade name: Epoxy curing agent

(Contd. of page 8)

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

#### · Department issuing MSDS: Product safety department

· Contact: Mr Eleazar dela Cruz

### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3