

Version number 2

Revision: 15.07.2016

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

- · Trade name: Epoxy resin
- · Article number: Cardolite FormuLITE 2501A
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- Product category PC9a Coatings and paints, thinners, paint removers
- · Application of the substance / the mixture Coating
- · 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: CARDOLITE SPECIALTY CHEMICALS EUROPE N.V. Wijmenstraat 21 K , Bus 2 9030 Mariakerke – Gent Tel. : +32 9 265.88.26 (Belgium) Fax. : +32 9 265.88.24 (Belgium) regulatory@cardolite.com eumsds@cardolite.com

· Further information obtainable from: Product safety department

• 1.4 Emergency telephone number: During business hours: +32 9 265.88.26 (Belgium)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

GHS07

Skin Irrit. 2	H315 Causes skin irritation.	
Eye Irrit. 2	H319 Causes serious eye irritation.	
Skin Sens. 1	H317 May cause an allergic skin reaction	n.

· 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



- · Signal word Warning
- **Hazard-determining components of labelling:** Liquid epoxy resin Cashew, nutshell liq., polymer with epichlorohydrin

(Contd. on page 2)

EU



Version number 2

Revision: 15.07.2016

Trade name: Epoxy resin

(Contd. of page 1)			
Hazard statements			
H315 Causes skin irritation.			
H319 Causes serious eye irritation.			
H317 May cause an allergic skin reaction.			
H411 Toxic to aquatic life with long lasting effects.			
· Precautionary statements			
P101 If medical advice is needed, have product container or label at hand.			
P102 Keep out of reach of children.			
P103 Read label before use.			
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.			
P280 Wear protective gloves/protective clothing/eye protection/face protection.			
P273 Avoid release to the environment.			
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact			
lenses, if present and easy to do. Continue rinsing.			
P321 Specific treatment (see on this label).			
P501 Dispose of contents/container in accordance with local/regional/national/international			
regulations.			
· Additional information:			
Contains epoxy constituents. May produce an allergic reaction.			
· 2.3 Other hazards			
· Results of PBT and vPvB assessment			
· PBT: Not applicable.			

• vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26-0031	Liquid epoxy resin Aquatic Chronic 2, H411; O Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	80,0 - 90,0%	
CAS: 68413-24-1 NLP: 500-210-7 Reg.nr.: 01-2119982994-15-0000	Cashew, nutshell liq., polymer with epichlorohydrin	10,0 - 20,0%	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)



Version number 2

Revision: 15.07.2016

Trade name: Epoxy resin

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. of page 2)

- **SECTION 5: Firefighting measures**
- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters Promptly isolate the scene by removing all person from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Not required. · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

- · 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- · 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

· Information about fire - and explosion protection: No special measures required.

 7.2 Conditions for safe storage, including any incompatibilities Keep container tightly closed and in a well ventilated place.

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Cardolite epoxy resins and hardeners may absorb moisture and carbon dioxide when left in open containers, which could result in increased viscosity, discoloration, reduction of reactivity, and/or crystallization of the products. These products should be kept tightly sealed in their original containers when not in use, and stored in a cool, dry place. Some Cardolite epoxy resins might crystallize. This reversible, physical phenomena can be greatly avoided by storing the resin at temperatures above 25 ℃.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)

EU



Version number 2

Revision: 15.07.2016

Trade name: Epoxy resin

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:
- The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eves and skin.
- · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- General Information
- · Appearance:
- Form:
 - Colour:

Liquid Light yellow



Version number 2

Revision: 15.07.2016

Trade name: Epoxy resin

	(Contd. of page 4
· Odour: · Odour threshold:	Mild Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
· Flash point:	> 250 ℃
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
Density at 25 °C:	1,138 g/cm ³
Relative density	Not determined.
 Vapour density Evaporation rate 	Not determined. Not determined.
-	Not determined.
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wat	er): Not determined.
· Viscosity:	
Dynamic at 25 ℃:	2000 - 2500 cps
Kinematic:	Not determined.
· Solvent content:	
Solids content:	> 98,0 %
 9.2 Other information 	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Product is stable.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 6)

ΕU



Version number 2

Revision: 15.07.2016

Trade name: Epoxy resin

(Contd. of page 5)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification: Irritating to eyes and skin.
- · Primary irritant effect:
- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms

12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 7)

EU



Version number 2

Revision: 15.07.2016

Trade name: Epoxy resin

(Contd. of page 6)

14.1 UN-Number ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name ADR IMDG	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product bisphenol-A-(epichlorhydrin) epoxy resin (numbe average molecular weight \leq 700)) ENVIRONMENTALLY HAZARDOUS SUBSTANCE
ΙΑΤΑ	LIQUID, N.O.S. (reaction product: bisphenol-A (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)), MARINE POLLUTANT Environmentally hazardous substance, liquid, n.o.s (reaction product: bisphenol-A-(epichlorhydrin epoxy resin (number average molecular weight 700))
14.3 Transport hazard class(es)	
ADR	
Class Label	9 Miscellaneous dangerous substances and articles Miscellaneous dangerous substances and articles. 9
IMDG, IATA	3
Class Label	9 Miscellaneous dangerous substances and articles 9
14.4 Packing group ADR, IMDG, IATA	111
14.5 Environmental hazards:	Product contains environmentally hazardou substances: reaction product: bisphenol-A (epichlorhydrin) epoxy resin (number averag- molecular weight ≤ 700)
Marine pollutant: Special marking (ADR): Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
Danger code (Kemler): EMS Number: Stowage Category	90 F-A,S-F A



Version number 2

Revision: 15.07.2016

Trade name: Epoxy resin

	(Contd. of page
 14.7 Transport in bulk according to Anno Marpol and the IBC Code 	ex II of Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m
 Transport category Tunnel restriction code 	3 E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (REACTIO PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN EPOXY RESIN (NUMBER AVERAGE MOLECULA WEIGHT \leq 700)), 9, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



- · Signal word Warning
- · Hazard-determining components of labelling:
- Liquid epoxy resin
- Cashew, nutshell liq., polymer with epichlorohydrin
- Hazard statements
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H411 Toxic to aquatic life with long lasting effects.
- Precautionary statements
- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 9)



Version number 2

Revision: 15.07.2016

Trade name: Epoxy resin

	D070	(Contd. of page 8)	
	P273 P305+P351+P338	Avoid release to the environment. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact	
	P321	lenses, if present and easy to do. Continue rinsing. Specific treatment (see on this label).	
	P501	Dispose of contents/container in accordance with local/regional/national/international regulations.	
-	Directive 2012/18	/EU	
		s substances - ANNEX I None of the ingredients is listed.	
		E2 Hazardous to the Aquatic Environment ty (tonnes) for the application of lower-tier requirements 200 t	
•	Qualifying quanti	ty (tonnes) for the application of upper-tier requirements 500 t	
		C) No 1907/2006 ANNEX XVII Conditions of restriction: 3 fety assessment: A Chemical Safety Assessment has not been carried out.	
	15.2 Chemical Sa	icy assessment. A chemical Salety Assessment has not been carried out.	
		Other information	
	any specific produc	based on our present knowledge. However, this shall not constitute a guarantee for ct features and shall not establish a legally valid contractual relationship.	
	Relevant phrases		
	H315 Causes skin	irritation. an allergic skin reaction.	
	H319 Causes serie		
	H411 Toxic to aqu	atic life with long lasting effects.	
		ng SDS: Product safety department	
	Contact: Mr Eleaz		
-		en sur le transport des marchandises dangereuses par Route (European Agreement concerning the	
		of Dangerous Goods by Road) aritime Code for Dangerous Goods	
	IATA: International Air	Transport Association	
		ised System of Classification and Labelling of Chemicals rentory of Existing Commercial Chemical Substances	
		t of Notified Chemical Substances cts Service (division of the American Chemical Society)	
	LC50: Lethal concentra	ation, 50 percent	
	LD50: Lethal dose, 50 PBT: Persistent, Bioac	cumulative and Toxic	
	vPvB: very Persistent a Skin Irrit, 2: Skin corros	and very Bioaccumulative sion/irritation – Category 2	
	Eye Irrit. 2: Serious eye	e damage/eye irritation – Category 2	
	Skin Sens. 1: Skin sen Aquatic Chronic 2: Haz	ardous to the aquatic environment - long-term aquatic hazard – Category 2	
		EU	