Cardolite[®] LITE 2100R CNSL Epoxy Modifier Preliminary Technical Datasheet

DESCRIPTION

Cardolite LITE 2100R is a EU REACH compliant, low viscosity, low color, cashew nutshell liquid modified hydrocarbon resin designed for use as an epoxy modifier in coatings, adhesives and composites. Similar to LITE 2100, LITE 2100R provides excellent dilution efficiency and improves compatibility and flexibility of the epoxy system while maintaining fast hardness development, very good chemical resistance and corrosion protection, and excellent adhesion even to unprepared surfaces.

PROPERTIES

| PROPERTY | TYPICAL VALUES | Test Method |
|----------------------------------------------|----------------|---------------|
| Color (Gardner) | ≤ 4 | ASTM D1544 |
| Viscosity @ 25°C (cPs) | 500 - 1,000 | ASTM D2196 |
| Volatile Content (% weight) | ≤ 1 | ASTM D2369-98 |
| Recommended Use Level (% resin) ¹ | ≤ 30 | |
| Density @ 25°C (kg/L) (lbs/gal) | 0.9803 8.18 | ASTM D1475 |
| Shelf Life (Months) | 12 | |

Optimum use level varies with application

APPLICATIONS

LITE 2100R enables high solids and solvent free protective and industrial coatings and construction adhesives such as grouts, self-levelers and mortars. LITE 2100R shows better dilution efficiency and less effect on dry time than typical phenol modified hydrocarbon resins, and it can increase hardness development of the coating while providing improved flexibility and impact resistance. The high hydrophobicity of this product results in excellent water and moisture resistance, and more importantly, excellent corrosion protection on immersed and vapor exposed surfaces. Laboratory evaluations demonstrated LITE 2100R exhibits good adhesion even to rusted metal substrates. Moreover, LITE 2100R shows very good UV resistance with excellent gloss retention for use in lighter color coatings. This renewable product can be used to replace aromatic hydrocarbon modifiers that are based solely on petrochemicals.

ADVANTAGES

- EU REACH polymer
- Excellent dilution power
- · Fast hardness development
- · Excellent flexibility and wetting
- · Good adhesion to poorly prepared surfaces
- Moisture tolerant
- Excellent water resistance

- · Good color and gloss retention
- Improves compatibility of epoxy system
- Superior corrosion protection
- Very good chemical resistance
- Non-toxic
- Based from natural, renewable, non-food chain raw material feedstock

REGULATORY STATUS

Please refer to the material safety data sheet (MSDS). Specific information regarding chemical inventory listing can be obtained from your local sales representative.

SAFETY PRECAUTIONS

Please refer to the material safety data sheet (MSDS). Copies of the MSDS can be requested on the Cardolite website or via your local sales representative.

STABILITY AND STORAGE

Cardolite products may absorb moisture and carbon dioxide when left in open containers, which could result in increased viscosity, discoloration, reduction of reactivity, and/or crystallization of the products. These products should be kept tightly sealed in their original containers when not in use, and stored in a cool, dry place.

CONTACT INFORMATION



Cardolite Corporation 500 Doremus Avenue Newark, NJ 07105 United States of America

T: +1-973-344-5015

Cardolite Specialty Chemicals Europe NV Wijmenstraat 21K / 2 B-9030 Mariakerke (Gent) Belgium

T: +32 (0) 92658826

Cardolite Specialty Chemicals India LLP Plot No. IP-1 & IP-2, Mangalore Special Economic Zone Bajpe, Mangalore 574 142, India

T: + 91 (0) 824 2888 300

http://www.cardolite.com

Cardolite Chemical Zhuhai Ltd. Biyang Road Harbor Industrial Zone Zhuhai, Guangdong 519050 P.R. China

T: +86-756-726-9066

DISCLAIMER & COPYRIGHT

All statements, technical information and recommendations contained herein are based on tests Cardolite believes to be reliable, but the accuracy or completeness thereof is not guaranteed. Actual test method procedures may differ from listed standards; major differences are noted. Limitation of liability and remedy: Purchase or use of these products constitutes an agreement with seller and manufacturer that, if the product proves to be defective or unsuitable, seller's and manufacturer's liability and the exclusive remedy, regardless of tort or contract theory or of incidental or consequential damages shall be to receive, at seller's or manufacturer's option, an equivalent quantity of replacement product or a refund of the purchase price. This datasheet is copyrighted to Cardolite Corporation and may be reproduced but not altered in any way.

Cardolite Preliminary Technical Datasheet LITE 2100R

Issue Date: 3/2016

Copyright © 2007-2016 Cardolite Corporation