

1 Identification

- **Product identifier**
- **Product Description: Epoxy curing agent**
- **Product code:** Cardolite LITE 3117
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Cardolite Corporation
 11 Deer Park Drive, Suite 124
 Monmouth Junction, NJ 08852
 USA
 Tel: (609)-436-0902
 Regulatory@cardolite.com
- **Information department:** Product safety department
- **Emergency telephone number:** +86532-83889090

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS05

- **Signal word** Danger

- **Hazard-determining components of labeling:**

1,3-Cyclohexanedimethanamine

- **Hazard statements**

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H318 Causes serious eye damage.

(Contd. on page 2)

Product Description: Epoxy curing agent

(Contd. of page 1)

Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 P241 Use explosion-proof electrical/ventilating/lighting/equipment.
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/doctor.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:
NFPA ratings (scale 0 - 4)

HMIS-ratings (scale 0 - 4)




Other hazards
Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients
Chemical characterization: Mixtures

- **Description:** Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

1330-20-7	xylene 	18.0 - 21.0%
2579-20-6	1,3-Cyclohexanedimethanamine 	2.0 - 5.0%
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol 	~ 1.5%

4 First-aid measures
Description of first aid measures
General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

Product Description: Epoxy curing agent

(Contd. of page 2)

- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

US

(Contd. on page 4)

Product Description: Epoxy curing agent

(Contd. of page 3)

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

- **Ingredients with biological limit values:**

1330-20-7 xylene

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Avoid contact with the skin.
 Avoid contact with the eyes and skin.

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Product Description: Epoxy curing agent

(Contd. of page 4)

 · **Eye protection:**


Tightly sealed goggles

 · **Body protection:** Protective work clothing

9 Physical and chemical properties

 · **Information on basic physical and chemical properties**

 · **General Information**

 · **Appearance:**

Form:	Liquid
Color:	Yellow-brown
Odor:	Amine-like
Odor threshold:	Not determined.

 · **pH-value at 25 °C (77 °F):** 10.5

 · **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	> 66 °C (> 151 °F)

 · **Flash point:** 32 °C (90 °F)

 · **Flammability (solid, gaseous):** Not applicable.

 · **Ignition temperature:**

Decomposition temperature: Not determined.

 · **Auto igniting:** Product is not selfigniting.

 · **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

 · **Explosion limits:**

Lower:	Not determined.
Upper:	Not determined.

 · **Vapor pressure:** Not determined.

 · **Density at 25 °C (77 °F):** 0.979 g/cm³ (8.17 lbs/gal)

 · **Relative density** Not determined.

 · **Vapor density** Not determined.

 · **Evaporation rate** Not determined.

 · **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

 · **Partition coefficient (n-octanol/water):** Not determined.

 · **Viscosity:**

Dynamic at 25 °C (77 °F):	~4500 cps
Kinematic:	Not determined.

 · **Solvent content:**

Solids content: ~ 80.0 %

(Contd. on page 6)


Product Description: Epoxy curing agent

(Contd. of page 5)

- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**
Irritating to eyes and skin.

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7 xylene	3
--------------------	---

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 7)

Product Description: Epoxy curing agent

(Contd. of page 6)

- **Additional ecological information:**
- **General notes:**
 Water hazard class 2 (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|----------------------------------|---------------------|
| · UN-Number | |
| · DOT, ADR, IMDG, IATA | UN1866 |
| · UN proper shipping name | |
| · DOT | Resin solution |
| · ADR | 1866 Resin solution |
| · IMDG, IATA | RESIN SOLUTION |

 · **Transport hazard class(es)**

 · **DOT**


- | | |
|----------------|---------------------|
| · Class | 3 Flammable liquids |
| · Label | 3 |

 · **ADR**


- | | |
|----------------|--|
| · Class | 3 Flammable liquids
Miscellaneous dangerous substances and articles |
| · Label | 3 |

(Contd. on page 8)

Product Description: Epoxy curing agent

(Contd. of page 7)

 · **IMDG, IATA**

 · **Class** 3 Flammable liquids
 · **Label** 3

 · **Packing group**
 · **DOT, ADR, IMDG, IATA** III

 · **Environmental hazards:**
 · **Marine pollutant:** No

 · **Special precautions for user** Warning: Flammable liquids
 · **Danger code (Kemler):** 33
 · **EMS Number:** F-E,S-E

 · **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

 · **UN "Model Regulation":** UN1866, Resin solution, 3, III

15 Regulatory information

 · **Safety, health and environmental regulations/legislation specific for the substance or mixture**
 · **Sara**

 · **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

 · **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

 · **TSCA (Toxic Substances Control Act):**

1330-20-7 xylene

2579-20-6 1,3-Cyclohexanedimethanamine

90-72-2 2,4,6-tris(dimethylaminomethyl)phenol

 · **Proposition 65**

 · **Chemicals known to cause cancer:**

None of the ingredients is listed.

 · **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

 · **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

 · **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

 · **Carcinogenic categories**

 · **EPA (Environmental Protection Agency)**

1330-20-7 xylene

I

(Contd. on page 9)

US

Product Description: Epoxy curing agent

(Contd. of page 8)

- **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene	A4
-----------	--------	----

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS05

- **Signal word** Danger

- **Hazard-determining components of labeling:**

1,3-Cyclohexanedimethanamine

- **Hazard statements**

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H318 Causes serious eye damage.

- **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Product safety department

- **Contact:** Mr Eleazar dela Cruz

- **Date of preparation / last revision** 05/19/2016 / 1

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 10)

**Cardolite**

Printing date 05/19/2016

Safety Data Sheet
acc. to OSHA HCS

Version 2

Reviewed on 05/19/2016

Product Description: Epoxy curing agent

(Contd. of page 9)

NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TVL: Treshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEL: Biological Exposure Limit
Flam. Liq. 3: Flammable liquids, Hazard Category 3
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

US