DESCRIPTION

Cardolite NC-342X is an elastomer modified, 80% solids resin in an aliphatic solvent blend used as a binder for friction products. Together with hexamine as cross-linking agent, NC-342X provides a heat-curable thermosetting resin system that offers all of the desirable characteristics of impact resistance, flexibility and thermal stability.

PROPERTIES

PROPERTY	SPECIFICATION	Test Method
Viscosity @ 25°C (cPs)	12,000 - 20,000	NTM 13
Gel time @ 82°C (min)	8 - 20	NTM 24
Gel particles (visual), particles/g	≤ 20	NTM 97
Solids (%)	78 - 82	NTM 7

PROPERTY	TYPICAL VALUE	TEST METHOD
Shelf Life (Months)	3	-
Density @ 25°C (kg/L) (lbs/gal)	0.91 7.6	NTM 62

Typical properties are not to be construed as specifications ¹ Based on total product weight

APPLICATIONS

Cardolite NC-342X provides very good processing viscosity and finds use in NAO applications that require high temperature stability and very good flexibility.

ADVANTAGES

Good processing viscosity

• Improved flexibility

Please refer to the material safety data sheet (MSDS). Specific information regarding chemical inventory listing can be obtained from your local sales representative.

SAFETY PRECAUTIONS

Please refer to the material safety data sheet (MSDS). Copies of the MSDS can be requested on the Cardolite website or via your local sales representative.

STABILITY AND STORAGE

Cardolite products may absorb moisture and carbon dioxide when left in open containers, which could result in increased viscosity, discoloration, reduction of reactivity, and/or crystallization of the products. These products should be kept tightly sealed in their original containers when not in use, and stored in a cool, dry place.

CONTACT INFORMATION



Cardolite Corporation 500 Doremus Avenue Newark, NJ 07105 United States of America Cardolite Specialty Chemicals Europe NV Wijmenstraat 21K / 2 B-9030 Mariakerke (Gent) Belgium

http://www.cardolite.com

T: +1-973-344-5015

T: +32 (0) 92658826

Cardolite Specialty Chemicals India Pvt. Ltd. Plot No. IP-1 & IP-2, Mangalore Special Economic Zone Bajpe, Mangalore 574 142, India T: + 91 (0) 824 4289 777 Cardolite Chemical Zhuhai Ltd. Biyang Road Harbor Industrial Zone Zhuhai, Guangdong 519050 P.R. China

T: +86-756-726-9066

DISCLAIMER & COPYRIGHT

All statements, technical information and recommendations contained herein are based on tests Cardolite believes to be reliable, but the accuracy or completeness thereof is not guaranteed. Actual test method procedures may differ from listed standards; major differences are noted. Limitation of liability and remedy: Purchase or use of these products constitutes an agreement with seller and manufacturer that, if the product proves to be defective or unsuitable, seller's and manufacturer's liability and the exclusive remedy, regardless of tort or contract theory or of incidental or consequential damages shall be to receive, at seller's or manufacturer's option, an equivalent quantity of replacement product or a refund of the purchase price. This datasheet is copyrighted to Cardolite Corporation and may be reproduced but not altered in any way.