

1 Identification

- **Product identifier**
- **Product Description: Epoxy Curing Agent**
- **Product code:** Cardolite NC-541LV
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Cardolite Corporation
11 Deer Park Drive, Suite 124
Monmouth Junction, NJ 08852
USA
Tel: (973) 344-5015
Regulatory@cardolite.com
- **Information department:** Product safety department
- **Emergency telephone number:** 24 Hour Emergency: 800-424-9300 CHEMTREC

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Flam. Liq. 4 H227 Combustible liquid.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Ethylenediamine

- **Hazard statements**

H227 Combustible liquid.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/20/2017

Version 3

Reviewed on 09/20/2017

Product Description: Epoxy Curing Agent

(Contd. of page 1)

- **Precautionary statements**

- P210 Keep away from flames and hot surfaces. – No smoking.
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray
 P284 [In case of inadequate ventilation] wear respiratory protection.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P321 Specific treatment (see on this label).
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 2
 Fire = 2
 Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



HEALTH 2 Health = *2
 FIRE 2 Fire = 2
 REACTIVITY 0 Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous Components:**

107-15-3	Ethylenediamine	~ 2.0%

4 First-aid measures

- **Description of first aid measures**

- **After inhalation:**

Supply fresh air and to be sure call for a doctor.
 In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

(Contd. on page 3)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 09/20/2017

Version 3

Reviewed on 09/20/2017

Product Description: Epoxy Curing Agent

(Contd. of page 2)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
Promptly isolate the scene by removing all person from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

107-15-3	Ethylenediamine	0.88 ppm
----------	-----------------	----------

- **PAC-2:**

107-15-3	Ethylenediamine	9.7 ppm
----------	-----------------	---------

- **PAC-3:**

107-15-3	Ethylenediamine	20 ppm
----------	-----------------	--------

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
- **Conditions for safe storage, including any incompatibilities**
Keep container tightly closed and in a well ventilated place.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.

(Contd. on page 4)

US

Product Description: Epoxy Curing Agent

(Contd. of page 3)

- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

Components with limit values that require monitoring at the workplace:
107-15-3 Ethylenediamine

PEL	Long-term value: 25 mg/m ³ , 10 ppm
REL	Long-term value: 25 mg/m ³ , 10 ppm
TLV	Long-term value: 25 mg/m ³ , 10 ppm
	Skin

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
Use local exhaust ventilation. Suitable respiratory equipment should be used in cases of insufficient ventilation.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

(Contd. on page 5)

Printing date 09/20/2017

Version 3

Reviewed on 09/20/2017

Product Description: Epoxy Curing Agent

(Contd. of page 4)

- **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Liquid
· Color:	Red-brown
· Odor:	Amine-like
· Odor threshold:	Not determined.

· **pH-value at 25 °C (77 °F):** 10.5

· **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	> 93 °C (>199.4 °F)

· **Flash point:** 70 °C (158 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:**

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Not determined.

· **Explosion limits:**

· Lower:	Not determined.
· Upper:	Not determined.

· **Vapor pressure:** Not determined.

· **Density at 25 °C (77 °F):** 0.98294 g/cm³ (8.20263 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

· **Water:** Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

· Dynamic at 25 °C (77 °F):	2300 CPS
· Kinematic:	Not determined.

· **Other information** No further relevant information available.

10 Stability and reactivity

· **Reactivity** No further relevant information available.

· **Chemical stability** Product is stable.

· **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

(Contd. on page 6)

Product Description: Epoxy Curing Agent

(Contd. of page 5)

- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**
Irritating to eyes and skin.

107-15-3 Ethylenediamine

Oral	LD50	866 mg/kg (rat)
Dermal	LD50	560 mg/kg (rabbit)
Inhalative	LC50/4 h	14.7 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:**
Sensitization possible through inhalation.
Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 7)

Printing date 09/20/2017

Version 3

Reviewed on 09/20/2017

Product Description: Epoxy Curing Agent

(Contd. of page 6)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|--|--|
| · UN-Number | |
| · DOT, ADR, ADN, IMDG, IATA | Non-hazardous for transport |
| · UN proper shipping name | |
| · DOT, ADR, ADN, IMDG, IATA | Non-hazardous for transport |
| · Transport hazard class(es) | |
| · DOT, ADN, IMDG, IATA | |
| · Class | Non-hazardous for transport |
| · ADR | |
| · Class | Non-hazardous for transport
Miscellaneous dangerous substances and articles |
| · Packing group | |
| · DOT, ADR, IMDG, IATA | Non-hazardous for transport |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | Non-hazardous for transport |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

 · **Section 355 (extremely hazardous substances):**

107-15-3	Ethylenediamine
----------	-----------------

 · **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

(Contd. on page 8)

Product Description: Epoxy Curing Agent

(Contd. of page 7)

- **TSCA (Toxic Substances Control Act):**

107-15-3 Ethylenediamine

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

107-15-3 Ethylenediamine

D

- **TLV (Threshold Limit Value established by ACGIH)**

107-15-3 Ethylenediamine

A4

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Ethylenediamine

- **Hazard statements**

H227 Combustible liquid.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

- **Precautionary statements**

P210 Keep away from flames and hot surfaces. – No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P284 [In case of inadequate ventilation] wear respiratory protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 9)

US

Product Description: Epoxy Curing Agent

(Contd. of page 8)

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Product safety department

- **Contact:** Mr Eleazar dela Cruz

- **Date of preparation / last revision** 09/20/2017 / 2

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TVL: Treshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Liq. 4: Flammable liquids – Category 4

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1