

Version 1 Reviewed on 02/09/2016

1 Identification

· Product identifier

· Product Description: Epoxy curing agent

· Product code: Cardolite NT-1545

• **CAS Number:** 68410-23-1

- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Cardolite Corporation 500 Doremus Avenue Newark, NJ 07105

USA

Tel: (973) 344-5015 Fax: (973) 344-1197 Regulatory@cardolite.com

- · Information department: Product safety department
- · Emergency telephone number: 24 Hour Emergency: 800-424-9300 CHEMTREC

2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The substance is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

Fatty Acids, C18-unsatd, dimers, reaction products with polyethylenepolyamines

Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

· Precautionary statements

P261

Avoid breathing dust/fume/gas/mist/vapors/spray

(Contd. on page 2)

Safety Data Sheet acc. to OSHA HCS

Version 1 Reviewed on 02/09/2016

Product Description: Epoxy curing agent

P280 Wear protective gloves.

(Contd. of page 1)

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Classification system:

NFPA ratings (scale 0 - 4)



Health = 2 Fire = 1 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *2 Fire = 1 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition/information on ingredients

- Chemical characterization: Substances
- · CAS No. Description

68410-23-1 Fatty Acids, C18-unsatd, dimers, reaction products with polyethylenepolyamines

4 First-aid measures

- Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.

(Contd. on page 3)

Safety Data Sheet acc. to OSHA HCS

Version 1 Reviewed on 02/09/2016

Product Description: Epoxy curing agent

(Contd. of page 2)

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters

Promptly isolate the scene by removing all person from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

· Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities

Keep container tightly closed and in a well ventilated place.

- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace: Not required.
- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

(Contd. on page 4)



Version 1 Reviewed on 02/09/2016

Product Description: Epoxy curing agent

· Breathing equipment:

(Contd. of page 3)

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Physical and chemical properties		
· Information on basic physical and · General Information	chemical properties	
· Appearance:		
Form:	Liquid	
Color:	Amber colored	
· Odor:	Ammonia-like	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. Undetermined.	
· Flash point:	182 ℃ (360 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:		
Decomposition temperature:	Not determined.	
· Auto igniting:	Not determined.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits: Lower:	Not determined.	

(Contd. on page 5)

Safety Data Sheet acc. to OSHA HCS

Version 1 Reviewed on 02/09/2016

Product Description: Epoxy curing agent

		(Contd. of page
Upper:	Not determined.	
Vapor pressure:	Not determined.	
Density at 25 °C (77 °F):	0.96 g/cm ³ (8.011 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wa	ater): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
VOC content:	2000 - 4000 cps	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Product is stable.
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

Irritating to eyes and skin.

68410-23-1 Fatty Acids, C18-unsatd, dimers, reaction products with polyethylenepolyamines

Oral LD50 5000 mg/kg (rat)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eve: Strong irritant with the danger of severe eve injury.
- · Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:
- Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

Substance is not listed.

· NTP (National Toxicology Program)

Substance is not listed.

(Contd. on page 6)



Version 1 Reviewed on 02/09/2016

Product Description: Epoxy curing agent

(Contd. of page 5)

· OSHA-Ca (Occupational Safety & Health Administration)

Substance is not listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · **Recommendation:** Disposal must be made according to official regulations.

· UN-Number	
· DOT, ADR, IMDG, IATA	UN3082
· UN proper shipping name	
DOT	Environmentally hazardous substances, liquid, n.o.s (Fatty Acids, C18-unsatd, dimers, reaction products wit polyethylenepolyamines)
· ADR	3082 Environmentally hazardous substances, liquic n.o.s. (Fatty Acids, C18-unsatd, dimers, reaction product with polyethylenepolyamines)
· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (Fatty Acids, C18-unsatd, dimers reaction products with polyethylenepolyamines), MARINI POLLUTANT

(Contd. on page 7)

Safety Data Sheet acc. to OSHA HCS

Version 1 Reviewed on 02/09/2016

Product Description: Epoxy curing agent

(Contd. of page 6) ·IATA Environmentally hazardous substance, liquid, n.o.s. (Fatty Acids, C18-unsatd, dimers, reaction products with polyethylenepolyamines) Transport hazard class(es) · DOT · Class 9 Miscellaneous dangerous substances and articles · Label · ADR · Class 9 Miscellaneous dangerous substances and articles Miscellaneous dangerous substances and articles · Label · IMDG, IATA · Class 9 Miscellaneous dangerous substances and articles · Label · Packing group DOT, ADR, IMDG, IATA Ш · Environmental hazards: · Marine pollutant: Symbol (fish and tree) Special marking (ADR): Symbol (fish and tree) · Special marking (IATA): Symbol (fish and tree) · Special precautions for user Warning: Miscellaneous dangerous substances and articles Stowage Category Α · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · DOT Quantity limitations On passenger aircraft/rail: No limit On cargo aircraft only: No limit · ADR Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml (Contd. on page 8)



Version 1 Reviewed on 02/09/2016

Product Description: Epoxy curing agent

(Contd. of page 7)

· IMDG

Limited quantities (LQ)Excepted quantities (EQ)

5L Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (FATTY ACIDS, C18-UNSATD, DIMERS, REACTION PRODUCTS WITH

POLYETHYLENEPOLYAMINES), 9, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

Substance is not listed.

· Section 313 (Specific toxic chemical listings):

Substance is not listed.

· TSCA (Toxic Substances Control Act):

Substance is listed.

· Proposition 65

· Chemicals known to cause cancer:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for females:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for males:

Substance is not listed.

· Chemicals known to cause developmental toxicity:

Substance is not listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

Substance is not listed.

· TLV (Threshold Limit Value established by ACGIH)

Substance is not listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

Substance is not listed.

· GHS label elements

The substance is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms





GHS05 GHS07

(Contd. of page 8)



Safety Data Sheet acc. to OSHA HCS

Version 1 Reviewed on 02/09/2016

Product Description: Epoxy curing agent

· Signal word Danger

· Hazard-determining components of labeling:

Fatty Acids, C18-unsatd, dimers, reaction products with polyethylenepolyamines

· Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

· Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: Mr Eleazar dela Cruz
- · Date of preparation / last revision 02/09/2016 / -
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TVL: Treshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1