

Version 2

Reviewed on 06/16/2015

1 Identification

- · Product identifier
- · Product Description: Epoxy curing agent
- · Product code: Cardolite NX-2016
- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Cardolite Corporation 500 Doremus Avenue Newark, NJ 07105 USA

Tel: (973) 344-5015 Fax: (973) 344-1197 edelacruz@cardolite.com

- · Information department: Product safety department
- · Emergency telephone number: 24 Hour Emergency: 800-424-9300 CHEMTREC

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



X Harmful

Harmful by inhalation and in contact with skin.



Irritant

Irritating to eyes and skin.

Flammable.

· Information concerning particular hazards for human and environment:

The product has to be labeled due to the calculation procedure of international guidelines.

· Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

(Contd. of page 1)

Cardolite Printing date 06/16/2015

Safety Data Sheet acc. to OSHA HCS

Version 2 Reviewed on 06/16/2015

Product Description: Epoxy curing agent

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling:

butanol

· Hazard statements

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H318 Causes serious eye damage.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 1 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1
 Fire = 3
 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

(Contd. on page 3)



Version 2 Reviewed on 06/16/2015

Product Description: Epoxy curing agent

		Contd. of page 2)
1330-20-7	xylene	17.0 - 21.0%
	Xn R20/21; Xi R38 R10	
	Flam. Liq. 3, H226; • Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
71-36-3	xn R22; xi R37/38-41	4.0 - 8.0%
	R10-67	
	♦ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	

4 First-aid measures

- Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters

Promptly isolate the scene by removing all person from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

· Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)

(Contd. of page 3)



Safety Data Sheet acc. to OSHA HCS

Version 2 Reviewed on 06/16/2015

Product Description: Epoxy curing agent

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

1330-20-7 xylene

PEL Long-term value: 435 mg/m³, 100 ppm

REL Short-term value: 655 mg/m³, 150 ppm

Long-term value: 435 mg/m³, 100 ppm

TLV Short-term value: 651 mg/m³, 150 ppm

Long-term value: 434 mg/m³, 100 ppm

BEI

71-36-3 butanol

PEL Long-term value: 300 mg/m³, 100 ppm

REL Ceiling limit value: 150 mg/m³, 50 ppm

Skin

TLV Long-term value: 61 mg/m³, 20 ppm

· Ingredients with biological limit values:

1330-20-7 xylene

BEI 1.5 g/g creatinine

Medium: urine Time: end of shift

Parameter: Methylhippuric acids

· Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)



Version 2 Reviewed on 06/16/2015

Product Description: Epoxy curing agent

(Contd. of page 4)

- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Color: Dark orange color • Odor: Amine-like

• Odour threshold: Not determined.

• **pH-value at 25 °C (77 °F):** 10.5

· Change in condition

Melting point/Melting range: Undetermined. Boiling point/Boiling range: $> 66 \, ^{\circ}\text{C} \, (> 151 \, ^{\circ}\text{F})$

• Flash point: 32 °C (90 °F)

(Contd. on page 6)



Version 2 Reviewed on 06/16/2015

Product Description: Epoxy curing agent

	(Contd. of page 5
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air vapor mixtures are possible.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 25 °C (77 °F):	0.99 g/cm³ (8.262 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/w	vater): Not determined.
· Viscosity:	
Dynamic at 25 ℃ (77 °F):	10.000 - 18.000 CPS
Kinematic:	Not determined.
· Solvent content:	
Solids content:	75.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- LD/LC50 values that are relevant for classification:

Irritating to eyes and skin.

1330-20-7 xylene			
Oral	LD50	4300 mg/kg (rat)	

(Contd. on page 7)

(Contd. of page 6)



Safety Data Sheet acc. to OSHA HCS

Version 2 Reviewed on 06/16/2015

Product Description: Epoxy curing agent

Dermal LD50 2000 mg/kg (rabbit)

· Primary irritant effect:

- · on the skin: Irritant to skin and mucous membranes.
- · on the eve: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1330-20-7 xylene

3

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

US



Version 2 Reviewed on 06/16/2015

Product Description: Epoxy curing agent

(Contd. of page 7)

4 Transport information	
· UN-Number · DOT, ADR, IMDG, IATA	UN1866
· UN proper shipping name · DOT · ADR · IMDG, IATA	Resin solution 1866 Resin solution RESIN SOLUTION
· Transport hazard class(es)	
- DOT	
· Class · Label	3 Flammable liquids 3
· ADR	
· Class	3 Flammable liquids Miscellaneous dangerous substances and articles
· Label	3
· IMDG, IATA	
· Class · Label	3 Flammable liquids 3
· Packing group · DOT, ADR, IMDG, IATA	III
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · Danger code (Kemler):	Warning: Flammable liquids
· EMS Number:	F-E <u>S-E</u>
	



Version 2 Reviewed on 06/16/2015

Product Description: Epoxy curing agent

(Contd. of page 8)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

71-36-3 butanol

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

1330-20-7 xylene I 71-36-3 butanol D

· TLV (Threshold Limit Value established by ACGIH)

1330-20-7 xylene A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms





GHS02 GHS05

- · Signal word Danger
- Hazard-determining components of labeling:

butanol

· Hazard statements

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H318 Causes serious eye damage.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 10)



Version 2 Reviewed on 06/16/2015

Product Description: Epoxy curing agent

(Contd. of page 9) P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: Mr Eleazar dela Cruz
- Date of preparation / last revision 06/16/2015 / 1
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3