

## 1 Identification

- **Product identifier**
- **Product Description:**  
Epoxy Curing Agent  
Epoxy Curing Agent
- **Product code:** Cardolite NT-5901
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Cardolite Corporation  
11 Deer Park Drive, Suite 124  
Monmouth Junction, NJ 08852  
USA  
Tel: (973) 344-5015  
Regulatory@cardolite.com
- **Information department:** Product safety department
- **Emergency telephone number:** 24 Hour Emergency: 800-424-9300 CHEMTREC

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS05 GHS07

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Benzyl Alcohol

3-Aminomethyl-3,5,5-Trimethylcyclohexylamine

- **Hazard statements**

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

**Product Description: Epoxy Curing Agent**

(Contd. of page 1)

**Precautionary statements**

- P260 Do not breathe dusts or mists.  
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P310 Immediately call a poison center/doctor.  
 P405 Store locked up.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Classification system:**
**NFPA ratings (scale 0 - 4)**


Health = 3  
 Fire = 1  
 Reactivity = 0

**HMIS-ratings (scale 0 - 4)**


Health = 3  
 Fire = 1  
 Reactivity = 0

**Other hazards**
**Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**3 Composition/information on ingredients**
**Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

**Dangerous Components:**

100-51-6	Benzyl Alcohol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332	> 40.0%
2855-13-2	3-Aminomethyl-3,5,5-Trimethylcyclohexylamine ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	< 30.0%

- **Additional information:** Non hazardous substance: Cycloaliphatic Amine 20.0 - 40.0%

**4 First-aid measures**
**Description of first aid measures**
**General information:**

Immediately remove any clothing soiled by the product.  
 Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

**After inhalation:**

Supply fresh air and to be sure call for a doctor.  
 In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

### Product Description: Epoxy Curing Agent

(Contd. of page 2)

- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**  
Immediately call a doctor.  
Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**  
Promptly isolate the scene by removing all person from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- **Protective equipment:** Mouth respiratory protective device.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralizing agent.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**  
Keep container tightly closed and in a well ventilated place.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.

(Contd. on page 4)

**Product Description: Epoxy Curing Agent**

(Contd. of page 3)

- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s):** No further relevant information available.

**8 Exposure controls/personal protection**

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.

**100-51-6 Benzyl Alcohol**

WEEL 10 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- **Breathing equipment:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

(Contd. on page 5)

US

**Product Description: Epoxy Curing Agent**

(Contd. of page 4)

- **Body protection:** Protective work clothing

**9 Physical and chemical properties**

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Liquid
Color:	Dark orange color
Odor:	Amine-like
Odor threshold:	Not determined.

- **pH-value at 25 °C (77 °F):** 9

- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	205 °C (401 °F)

- **Flash point:** 96 °C (204.8 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:**

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product does not present an explosion hazard.

- **Explosion limits:**

Lower:	Not determined.
Upper:	Not determined.

- **Vapor pressure:** Not determined.

- **Density at 25 °C (77 °F):** 0.99696 g/cm<sup>3</sup> (8.31963 lbs/gal)

- **Relative density** Not determined.

- **Vapor density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

- **Water:** Not miscible or difficult to mix.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

Dynamic:	Not determined.
Kinematic:	Not determined.

- **Other information** No further relevant information available.

**10 Stability and reactivity**

- **Reactivity** No further relevant information available.

- **Chemical stability** Product is stable.

- **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

(Contd. on page 6)

**Product Description: Epoxy Curing Agent**

(Contd. of page 5)

- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

**11 Toxicological information**

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**  
Irritating to eyes and skin.

**100-51-6 Benzyl Alcohol**

Oral	LD50	1230 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:** Strong caustic effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Harmful  
Corrosive  
Irritant  
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (Self-assessment): slightly hazardous for water

(Contd. on page 7)

**Safety Data Sheet**  
 acc. to OSHA HCS

Printing date 11/02/2017

Version 2

Reviewed on 11/02/2017

**Product Description: Epoxy Curing Agent**

(Contd. of page 6)

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Harmful to aquatic organisms

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

- **UN-Number**

- **DOT, ADR, IMDG, IATA** UN2735

- **UN proper shipping name**

- **DOT**

- **ADR**

- **IMDG, IATA**

Amines, liquid, corrosive, n.o.s. (Isophoronediamine)  
 2735 Amines, liquid, corrosive, n.o.s.  
 (Isophoronediamine)  
 AMINES, LIQUID, CORROSIVE, N.O.S.  
 (ISOPHORONEDIAMINE)

- **Transport hazard class(es)**

- **DOT**



- **Class**

8 Corrosive substances

- **Label**

8

- **ADR, IMDG, IATA**



- **Class**

8 Corrosive substances

- **Label**

8

- **Packing group**

- **DOT, ADR, IMDG, IATA** III

(Contd. on page 8)

Printing date 11/02/2017

Version 2

Reviewed on 11/02/2017

**Product Description: Epoxy Curing Agent**

(Contd. of page 7)

<ul style="list-style-type: none"> <li>• <b>Environmental hazards:</b></li> <li>• <b>Marine pollutant:</b></li> </ul>	<p>No</p>
<ul style="list-style-type: none"> <li>• <b>Special precautions for user</b></li> <li>• <b>Danger code (Kemler):</b></li> <li>• <b>EMS Number:</b></li> <li>• <b>Segregation groups</b></li> </ul>	<p>Warning: Corrosive substances 80 F-A,S-B Alkalis</p>
<ul style="list-style-type: none"> <li>• <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b></li> </ul>	<p>Not applicable.</p>
<ul style="list-style-type: none"> <li>• <b>Transport/Additional information:</b></li> <li>• <b>DOT</b></li> <li>• <b>Quantity limitations</b></li> </ul>	<p>On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L</p>
<ul style="list-style-type: none"> <li>• <b>ADR</b></li> <li>• <b>Excepted quantities (EQ)</b></li> </ul>	<p>Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p>
<ul style="list-style-type: none"> <li>• <b>IMDG</b></li> <li>• <b>Limited quantities (LQ)</b></li> <li>• <b>Excepted quantities (EQ)</b></li> </ul>	<p>5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p>
<ul style="list-style-type: none"> <li>• <b>UN "Model Regulation":</b></li> </ul>	<p>UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (ISOPHORONEDIAMINE), 8, III</p>

**15 Regulatory information**

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

(Contd. on page 9)



**Product Description: Epoxy Curing Agent**

(Contd. of page 8)

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

- **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS05 GHS07

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Benzyl Alcohol

3-Aminomethyl-3,5,5-Trimethylcyclohexylamine

- **Hazard statements**

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

- **Precautionary statements**

P260 Do not breathe dusts or mists.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Product safety department

- **Contact:** Mr Eleazar dela Cruz

- **Date of preparation / last revision** 11/02/2017 / 1

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 10)

**Product Description: Epoxy Curing Agent**

(Contd. of page 9)

CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
TVL: Treshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Corr. 1B: Skin corrosion/irritation – Category 1B  
Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
Skin Sens. 1: Skin sensitisation – Category 1

US