

Printing date 29.11.2017 Version number 2 Revision: 29.11.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Epoxy Curing Agent
- · Article number: Cardolite NX-5594
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- · Product category PC9a Coatings and paints, thinners, paint removers
- · Application of the substance / the mixture Coating
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

CARDOLITE SPECIALTY CHEMICALS EUROPE N.V.

Wijmenstraat 21 K , Bus 2 9030 Mariakerke – Gent

Tel.: +32 9 265.88.26 (Belgium) Fax.: +32 9 265.88.24 (Belgium)

regulatory@cardolite.com eumsds@cardolite.com

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: During business hours: +32 9 265.88.26 (Belgium)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS05 GHS07

· Signal word Danger



Printing date 29.11.2017 Version number 2 Revision: 29.11.2017

Trade name: Epoxy Curing Agent

(Contd. of page 1)

· Hazard-determining components of labelling:

m-Phenylenebis(methylamine)

Trimethylhexane-1,6-Diamine

Hazard statements

H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P260 Do not breathe dusts or mists.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50-0000	m-Phenylenebis(methylamine) Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412	20.0 - 35.0%
CAS: 25620-58-0 EINECS: 247-134-8	Trimethylhexane-1,6-Diamine Skin Corr. 1B, H314; Acute Tox. 4, H302; Skin Sens. 1, H317	5.0 - 15.0%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)



Printing date 29.11.2017 Version number 2 Revision: 29.11.2017

Trade name: Epoxy Curing Agent

(Contd. of page 2)

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters

Promptly isolate the scene by removing all person from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

· Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Ose neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed and in a well ventilated place.

- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)



Printing date 29.11.2017 Version number 2 Revision: 29.11.2017

Trade name: Epoxy Curing Agent

(Contd. of page 3)

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

Use local exhaust ventilation. Suitable respiratory equipment should be used in cases of insufficient ventilation.

· Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

(Contd. on page 5)



Printing date 29.11.2017 Version number 2 Revision: 29.11.2017

Trade name: Epoxy Curing Agent

	(Contd. of page 4)
Colour: · Odour: · Odour threshold:	Light yellow Amine-like Not determined.
· pH-value at 25 °C:	10.5
 Change in condition Melting point/freezing point: Initial boiling point and boiling range: 	Undetermined. : Undetermined.
· Flash point:	> 104 ℃
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
 Explosion limits: Lower: Upper: 	Not determined. Not determined.
· Vapour pressure:	Not determined.
 Density at 25 °C: Relative density Vapour density Evaporation rate 	1.02571 g/cm ³ Not determined. Not determined. Not determined.
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic at 25 ℃: Kinematic:	1150 cps Not determined.
· Solvent content:	
Solids content: • 9.2 Other information	> 98.0 % No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability Product is stable.
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6)



Printing date 29.11.2017 Version number 2 Revision: 29.11.2017

Trade name: Epoxy Curing Agent

(Contd. of page 5)

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if inhaled.

· LD/LC50 values relevant for classification:

Irritating to eyes and skin.

Oral	LD50	1,040 mg/kg (rat)
Inhalative	LC50/4 h	2.4 mg/l (rat)

25620-58-0 Trimethylhexane-1,6-Diamine

Oral LD50 900 mg/kg (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

U



Printing date 29.11.2017 Version number 2 Revision: 29.11.2017

Trade name: Epoxy Curing Agent

(Contd. of page 6)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
· 14.1 UN-Number · ADR, IMDG, IATA	UN2735
· 14.2 UN proper shipping name · ADR · IMDG, IATA	2735 AMINES, LIQUID, CORROSIVE, N.O.S. (mphenylenebis (methylamine); TRIMETHYLHEXAMETHYLENEDIAMINES) AMINES, LIQUID, CORROSIVE, N.O.S. (mphenylenebis (methylamine); TRIMETHYLHEXAMETHYLENEDIAMINES)
· 14.3 Transport hazard class(es)	
· ADR	
· Class	8 Corrosive substances. Miscellaneous dangerous substances and articles. 8
· IMDG, IATA	
· Class · Label	8 Corrosive substances.
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	No
 · 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category · Segregation Code 	Warning: Corrosive substances. 80 F-A,S-B A SG35 Stow "separated from" acids.



Printing date 29.11.2017 Version number 2 Revision: 29.11.2017

Trade name: Epoxy Curing Agent

(Contd. of page
nex II of Not applicable.
5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
3
E
5 L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
UN2735, AMINES, LIQUID, CORROSIVE, N.O.S
(m-phenylenebis (methylamine)
TRIMETHYLHEXAMETHYLENEDIAMINES), 8, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

m-Phenylenebis(methylamine)

Trimethylhexane-1,6-Diamine

Hazard statements

H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P260 Do not breathe dusts or mists.

(Contd. on page 9)



Printing date 29.11.2017 Version number 2 Revision: 29.11.2017

Trade name: Epoxy Curing Agent

(Contd. of page 8)

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.

H314 Causes severe skin burns and eve damage.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H412 Harmful to aquatic life with long lasting effects.

- · Department issuing SDS: Product safety department
- · Contact: Mr Eleazar dela Cruz
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3