

Version 1

Printing date 12/21/2017

Reviewed on 12/21/2017

## **1** Identification

- Product identifier
- · Product Description: Epoxy Curing Agent
- · Product code: Cardolite FormuLITE 2405B
- · Application of the substance / the mixture Coating
- Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Cardolite Corporation 11 Deer Park Drive, Suite 124 Monmouth Junction, NJ 08852 USA Tel: (973) 344-5015 Regulatory@cardolite.com

· Information department: Product safety department

· Emergency telephone number: 24 Hour Emergency: 800-424-9300 CHEMTREC

## 2 Hazard(s) identification

#### · Classification of the substance or mixture

**GHS05** Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eve Dam. 1 H318 Causes serious eye damage.



Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Danger

- · Hazard-determining components of labeling: 3-Aminomethyl-3,5,5-Trimethylcyclohexylamine m-Phenylenebis(methylamine) Salicylic acid 3,6-diazaoctanethylenediamin 3,6,9-Triazaundecamethylenediamine · Hazard statements H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.

(Contd. on page 2)



Version 1

Reviewed on 12/21/2017

## **Product Description: Epoxy Curing Agent**

Printing date 12/21/2017

(Contd. of page 1)
tements
Do not breathe dusts or mists.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center/doctor.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
tem:
le 0 - 4)
n = 3 1 ivity = 0
le 0 - 4)
th = *3 = 1 stivity = 0
id vPvB assessment
e.
ble.

## 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

2855-13-2	3-Aminomethyl-3,5,5-Trimethylcyclohexylamine	10.0 - 20.0%
	Skin Corr. 1B, H314; () Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	
1477-55-0	m-Phenylenebis(methylamine)	10.0 - 15.0%
	Skin Corr. 1B, H314;  Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1B, H317	
69-72-7	Salicylic acid	5.0 - 10.0%
	Eye Dam. 1, H318; () Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335	
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	1.0 - 5.0%
	Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2A, H319	
112-24-3	3,6-diazaoctanethylenediamin	1.0 - 5.0%
	Skin Corr. 1B, H314; () Acute Tox. 4, H312; Skin Sens. 1, H317	
112-57-2	3,6,9-Triazaundecamethylenediamine	< 1.0%
	♦ Skin Corr. 1B, H314; ♦ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317	

(Contd. on page 3)



Printing date 12/21/2017

### Version 1

Reviewed on 12/21/2017

#### Product Description: Epoxy Curing Agent

(Contd. of page 2)

- US

## 4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- Advice for firefighters Promptly isolate the scene by removing all person from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- · Protective equipment: Mouth respiratory protective device.

## 6 Accidental release measures

Mount res Wear prov Environn Methods Absorb wi Use neutr Dispose of Ensure ac Referenc See Secti See Secti See Secti	<ul> <li>precautions, protective equipment and emergency procedures</li> <li>piratory protective device.</li> <li>tective equipment. Keep unprotected persons away.</li> <li>nental precautions: Do not allow to enter sewers/ surface or ground water.</li> <li>and material for containment and cleaning up:</li> <li>th liquid-binding material (sand, diatomite, acid binders, universal binders, saw alizing agent.</li> <li>contaminated material as waste according to item 13.</li> <li>dequate ventilation.</li> <li>e to other sections</li> <li>on 7 for information on safe handling.</li> <li>on 8 for information on personal protection equipment.</li> <li>on 13 for disposal information.</li> <li>e Action Criteria for Chemicals</li> </ul>	dust).
· PAC-1:		
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	6.5 mg/m <sup>3</sup>
112-24-3	3,6-diazaoctanethylenediamin	3 ppm
112-57-2	3,6,9-Triazaundecamethylenediamine	15 mg/m <sup>3</sup>
		(Contd. on page 4)



Printing date 12/21/2017

Version 1

### Product Description: Epoxy Curing Agent

		(Contd. of page 3
PAC-2:		
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	72 mg/m <sup>3</sup>
112-24-3	3,6-diazaoctanethylenediamin	14 ppm
112-57-2	3,6,9-Triazaundecamethylenediamine	130 mg/m <sup>3</sup>
PAC-3:		
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	430 mg/m <sup>3</sup>
112-24-3	3,6-diazaoctanethylenediamin	83 ppm
112-57-2	3,6,9-Triazaundecamethylenediamine	790 mg/m <sup>3</sup>

## 7 Handling and storage

- · Handling:
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep respiratory protective device available.
- Conditions for safe storage, including any incompatibilities Keep container tightly closed and in a well ventilated place.
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

## 112-24-3 3,6-diazaoctanethylenediamin

WEEL Long-term value: 6 mg/m<sup>3</sup>, 1 ppm Skin

## 112-57-2 3,6,9-Triazaundecamethylenediamine

```
WEEL Long-term value: 5 mg/m<sup>3</sup>
Skin; DSEN
```

• Additional information: The lists that were valid during the creation were used as basis.

#### · Exposure controls

Use local exhaust ventilation. Suitable respiratory equipment should be used in cases of insufficient ventilation.

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing.

(Contd. on page 5)

US

(Contd. of page 4)



Printing date 12/21/2017

Version 1

Reviewed on 12/21/2017

## **Product Description: Epoxy Curing Agent**

Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

<ul> <li>Information on basic physical and</li> <li>General Information</li> <li>Appearance:</li> </ul>	chemical properties	
Form:	Liquid	
Color:	Yellow tint	
Odor:	Amine-like	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Undetermined.	
Flash point:	98 ℃ (208.4 °F)	
· Flammability (solid, gaseous):	Not applicable.	



Printing date 12/21/2017

#### Version 1

Reviewed on 12/21/2017

#### Product Description: Epoxy Curing Agent

	(Contd. of page
Ignition temperature:	
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits: Lower: Upper:	Not determined. Not determined.
Vapor pressure:	Not determined.
Density at 25 °C (77 °F): Relative density Vapor density Evaporation rate	1.14 g/cm <sup>3</sup> (9.5133 lbs/gal) Not determined. Not determined. Not determined.
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wa	ter): Not determined.
Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
Other information	No further relevant information available.

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Product is stable.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- LD/LC50 values that are relevant for classification: Irritating to eyes and skin.

## 1477-55-0 m-Phenylenebis(methylamine)

Oral LD50 1,040 mg/kg (rat)

## Inhalative LC50/4 h 2.4 mg/l (rat)

## 69-72-7 Salicylic acid

Oral LD50 891 mg/kg (rat)

(Contd. on page 7)

US



Printing date 12/21/2017

## Version 1

Reviewed on 12/21/2017

## Product Description: Epoxy Curing Agent

90-72-2 2	.4.6-Tris(	(Contd. of page 6 Dimethylaminomethyl)Phenol
Oral	LD50	2,169 mg/kg (rat)
Dermal	LD50	1,260 mg/kg (rabbit)
112-24-3	3,6-diaza	octanethylenediamin
Oral	LD50	2,500 mg/kg (rat)
Dermal	LD50	805 mg/kg (rabbit)
112-57-2	3,6,9-Tria	zaundecamethylenediamine
Dermal	LD50	660 mg/kg (rabbit)
		sitization possible through skin contact.
Additiona The prod preparation Corrosive Irritant Swallowin esophagu	al toxicol uct show ons: ng will lea is and sto	ogical information: s the following dangers according to internally approved calculation methods fo d to a strong caustic effect on mouth and throat and to the danger of perforation o mach.
Additiona The prod preparatio Corrosive Irritant Swallowin esophagu Carcinog	al toxicolo uct show ons: ng will lead us and sto genic cate	ogical information: s the following dangers according to internally approved calculation methods fo d to a strong caustic effect on mouth and throat and to the danger of perforation of mach. gories
<ul> <li>Additiona</li> <li>The prod</li> <li>preparatio</li> <li>Corrosive</li> <li>Irritant</li> <li>Swallowin</li> <li>esophagu</li> <li>Carcinog</li> <li>IARC (Interpretation)</li> </ul>	al toxicolo uct show ons: ng will lea is and sto jenic cate ernationa	begical information: s the following dangers according to internally approved calculation methods for d to a strong caustic effect on mouth and throat and to the danger of perforation of mach. Begories al Agency for Research on Cancer)
Additiona The prod preparatio Corrosive Irritant Swallowin esophagu Carcinog IARC (Int None of t	al toxicolo uct show ons: ng will lead is and sto genic cate rernationa he ingredi	by the following dangers according to internally approved calculation methods for d to a strong caustic effect on mouth and throat and to the danger of perforation of mach. By a strong caustic effect on Cancer a Agency for Research on Cancer) ents is listed.
<ul> <li>Additiona</li> <li>The prod</li> <li>preparatio</li> <li>Corrosive</li> <li>Irritant</li> <li>Swallowin</li> <li>esophagu</li> <li>Carcinog</li> <li>IARC (Int</li> <li>None of t</li> <li>NTP (Nat</li> </ul>	al toxicole uct shows ons: ng will lead is and sto genic cate ernationa he ingredi ional Tox	by the following dangers according to internally approved calculation methods for d to a strong caustic effect on mouth and throat and to the danger of perforation of mach. By Bories al Agency for Research on Cancer)

None of the ingredients is listed.

## 12 Ecological information

- Toxicity
- Aquatic toxicity: No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 8)

US

Version 1

#### Product Description: Epoxy Curing Agent

· Other adverse effects No further relevant information available.

## 13 Disposal considerations

· Waste treatment methods


### · Recommendation:

Printing date 12/21/2017

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.





/11 1

(Contd. of page 7)



Printing date 12/21/2017

Version 1

Reviewed on 12/21/2017

## Product Description: Epoxy Curing Agent

	(Contd. of page
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards:	Not applicable.
Special precautions for user Danger code (Kemler): EMS Number: Segregation groups Stowage Category Segregation Code	Warning: Corrosive substances 80 F-A,S-B Alkalis A SG35 Stow "separated from" acids.
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	t <b>II of</b> Not applicable.
Transport/Additional information:	
рот	
Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
ADR	
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (N P H E N Y L E N E B I S ( M E T H Y L A M I N E ) ISOPHORONEDIAMINE), 8, III

# 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture
· Sara

<ul> <li>Section 355 (extremely hazardous substances):</li> </ul>	
None of the ingredients is listed.	
<ul> <li>Section 313 (Specific toxic chemical listings):</li> </ul>	
None of the ingredients is listed.	
· TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
<ul> <li>TSCA new (21st Century Act) (Substances not listed)</li> </ul>	
1477-55-0 m-Phenylenebis(methylamine)	
· Proposition 65	
<ul> <li>Chemicals known to cause cancer:</li> </ul>	
None of the ingredients is listed.	
	(Contd. on page 10)
	112

US



Printing date 12/21/2017

## Safety Data Sheet acc. to OSHA HCS

Version 1

Reviewed on 12/21/2017

## Product Description: Epoxy Curing Agent

Chamicala kna	(Contd. of pa
	wn to cause reproductive toxicity for females: edients is listed.
	wn to cause reproductive toxicity for males:
	edients is listed.
	wn to cause developmental toxicity:
None of the ing	edients is listed.
· Carcinogenic o	ategories
•	ental Protection Agency)
None of the ing	edients is listed.
TLV (Threshole	I Limit Value established by ACGIH)
None of the ing	edients is listed.
· NIOSH-Ca (Nat	ional Institute for Occupational Safety and Health)
None of the ing	edients is listed.
$\land$	
GHS05 GHS	707
GHS05 GHS	
• Signal word Da • Hazard-determ 3-Aminomethyl- m-Phenylenebis Salicylic acid 3,6-diazaoctane 3,6,9-Triazauno	inger ining components of labeling: 3,5,5-Trimethylcyclohexylamine (methylamine) thylenediamin ecamethylenediamine
<ul> <li>Signal word Data</li> <li>Hazard-determ</li> <li>3-Aminomethyl-</li> <li>m-Phenylenebis</li> <li>Salicylic acid</li> <li>3,6-diazaoctane</li> <li>3,6,9-Triazauno</li> <li>Hazard statem</li> <li>H314 Causes s</li> <li>H317 May caus</li> </ul>	inger ining components of labeling: 3,5,5-Trimethylcyclohexylamine (methylamine) thylenediamin ecamethylenediamine ents evere skin burns and eye damage. e an allergic skin reaction.
<ul> <li>Signal word Data</li> <li>Hazard-determ</li> <li>3-Aminomethyl-</li> <li>m-Phenylenebis</li> <li>Salicylic acid</li> <li>3,6-diazaoctane</li> <li>3,6-9-Triazauno</li> <li>Hazard statem</li> <li>H314 Causes s</li> <li>H317 May caus</li> <li>Precautionary</li> <li>P260</li> </ul>	inger ining components of labeling: 3,5,5-Trimethylcyclohexylamine (methylamine) thylenediamin ecamethylenediamine ents evere skin burns and eye damage. e an allergic skin reaction. statements Do not breathe dusts or mists. 53 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin
<ul> <li>Signal word Data</li> <li>Hazard-determ</li> <li>3-Aminomethyl- m-Phenylenebis</li> <li>Salicylic acid</li> <li>3,6-diazaoctane</li> <li>3,6-diazaoctane</li> <li>3,6-9-Triazauno</li> <li>Hazard statem</li> <li>H314 Causes s</li> <li>H317 May caus</li> <li>Precautionary</li> <li>P260</li> <li>P303+P361+P3</li> </ul>	inger ining components of labeling: 3,5,5-Trimethylcyclohexylamine (methylamine) thylenediamin ecamethylenediamine ents evere skin burns and eye damage. e an allergic skin reaction. statements Do not breathe dusts or mists.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- US



Printing date 12/21/2017

## Version 1

Reviewed on 12/21/2017

## Product Description: Epoxy Curing Agent

(Contd. of page 10
Department issuing SDS: Product safety department
· Contact: Mr Eleazar dela Cruz
Date of preparation / last revision 12/21/2017 / -
Abbreviations and acronyms:
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning th
International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TVL: Treshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3