

Printing date 01/16/2018 Version 3 Reviewed on 01/16/2018

1 Identification

- · Product identifier
- · Product Description: Epoxy Curing Agent
- · Product code: Cardolite LITE 3060
- Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Cardolite Corporation

11 Deer Park Drive, Suite 124 Monmouth Junction, NJ 08852

USA

Tel: (973) 344-5015 Regulatory@cardolite.com

- · Information department: Product safety department
- · Emergency telephone number: 24 Hour Emergency: 800-424-9300 CHEMTREC

2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



Skin Sens. 1 H317 May cause an allergic skin reaction.

Flam. Liq. 4 H227 Combustible liquid.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:
- 1,3-Cyclohexanedimethanamine
- 3-Aminopropyldimethylamine

Salicylic acid

· Hazard statements

H227 Combustible liquid.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

(Contd. on page 2)



Printing date 01/16/2018 Version 3 Reviewed on 01/16/2018

Product Description: Epoxy Curing Agent

(Contd. of page 1)

Precautionary statements

P210 Keep away from flames and hot surfaces. – No smoking.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 2 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *2 Fire = 2

Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous Components:				
2579-20-6	1,3-Cyclohexanedimethanamine Skin Corr. 1A, H314; Acute Tox. 4, H302; Acute Tox. 4, H312	5.0 - 9.0%		
109-55-7	3-Aminopropyldimethylamine ♦ Flam. Liq. 3, H226; ♦ Skin Corr. 1B, H314; ♦ Acute Tox. 4, H302; Skin Sens. 1, H317	3.0 - 8.0%		
69-72-7	Salicylic acid Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335	1.0 - 3.0%		

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)



Printing date 01/16/2018 Version 3 Reviewed on 01/16/2018

Product Description: Epoxy Curing Agent

(Contd. of page 2)

- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

· Advice for firefighters

Promptly isolate the scene by removing all person from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

· Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

· PAC-1:	
109-55-7 3-Aminopropyldimethylamine	1.2 ppm
· PAC-2:	
109-55-7 3-Aminopropyldimethylamine	13 ppm
· PAC-3:	
109-55-7 3-Aminopropyldimethylamine	89 ppm

7 Handling and storage

- · Handling:
- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

(Contd. on page 4)



Printing date 01/16/2018 Version 3 Reviewed on 01/16/2018

Product Description: Epoxy Curing Agent

(Contd. of page 3)

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

Keep container tightly closed and in a well ventilated place.

- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

Use local exhaust ventilation. Suitable respiratory equipment should be used in cases of insufficient ventilation.

- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

(Contd. of page 4)



Safety Data Sheet acc. to OSHA HCS

Printing date 01/16/2018 Version 3 Reviewed on 01/16/2018

Product Description: Epoxy Curing Agent

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid
Color: Yellow
Odor: Amine-like
Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined. Boiling point/Boiling range: Undetermined.

• Flash point: $> 61 \degree C (>141.8 \degree F)$

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature:

Decomposition temperature: Not determined.

· **Auto igniting:** Product is not selfigniting.

· Danger of explosion: Not determined.

· Explosion limits:

Lower: Not determined. **Upper:** Not determined.

· Vapor pressure: Not determined.

• **Density at 25 °C (77 °F):** 0.95981 g/cm³ (8.00961 lbs/gal)

Relative density
 Vapor density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic at 25 °C (77 °F): 500 - 1000 cps **Kinematic:** Not determined.

• Other information No further relevant information available.



Printing date 01/16/2018 Version 3 Reviewed on 01/16/2018

Product Description: Epoxy Curing Agent

(Contd. of page 5)

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Product is stable.
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- LD/LC50 values that are relevant for classification:

Irritating to eves and skin.

intating to eyes and skin.		
2579-20-6 1,3-Cyclohexanedimethanamine		
Oral	LD50	700 mg/kg (rat)
Dermal	LD50	1,700 mg/kg (rabbit)
109-55-7 3-Aminopropyldimethylamine		
Oral	LD50	1,870 mg/kg (rat)
Dermal	LD50	490 mg/kg (rabbit)
69-72-7 Salicylic acid		
Oral	LD50	891 mg/kg (rat)
Oral Dermal 69-72-7	LD50 LD50 Salicy	1,870 mg/kg (rat) 490 mg/kg (rabbit) /lic acid

- · Primary irritant effect:
- on the skin: Strong caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.



Printing date 01/16/2018 Version 3 Reviewed on 01/16/2018

Product Description: Epoxy Curing Agent

(Contd. of page 6)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

- Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.

	14 Trans	oort infor	mation
--	----------	------------	--------

· UN-Number · DOT, ADR, IMDG, IATA	UN2735
· UN proper shipping name	
DOT	Amines, liquid, corrosive, n.o.s. (3-Aminopropyldimethylamine)
· ADR	2735 Amines, liquid, corrosive, n.o.s. (3-Aminopropyldimethylamine)
· IMDG, IATA	AMINES, LIQUID, CORROSIVE, N.O.S. (3-Aminopropyldimethylamine)

- Transport hazard class(es)
- · DOT



Class
 8 Corrosive substances

(Contd. on page 8)



Printing date 01/16/2018 Version 3 Reviewed on 01/16/2018

8

Product Description: Epoxy Curing Agent

(Contd. of page 7)

· Label

· ADR



· Class 8 Corrosive substances

Miscellaneous dangerous substances and articles

· Label

· IMDG, IATA



Class
 8 Corrosive substances

· Label

· Packing group

· DOT, ADR, IMDG, IATA

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Warning: Corrosive substances

Danger code (Kemler): 80
EMS Number: F-A,S-B

Segregation groupsStowage CategoryAlkalis

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· DOT

• Quantity limitations On passenger aircraft/rail: 1 L

On cargo aircraft only: 60 L

· ADR

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· IMDG

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (3-

AMINOPROPYLDIMETHYLAMINE), 8, III



Printing date 01/16/2018 Version 3 Reviewed on 01/16/2018

Product Description: Epoxy Curing Agent

(Contd. of page 8)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

2579-20-6 1,3-Cyclohexanedimethanamine

109-55-7 3-Aminopropyldimethylamine

69-72-7 Salicylic acid

- · TSCA new (21st Century Act) (Substances not listed)
- Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:
- 1,3-Cyclohexanedimethanamine
- 3-Aminopropyldimethylamine

Salicylic acid

· Hazard statements

H227 Combustible liquid.

H314 Causes severe skin burns and eye damage.



Printing date 01/16/2018 Version 3 Reviewed on 01/16/2018

Product Description: Epoxy Curing Agent

(Contd. of page 9)

H317 May cause an allergic skin reaction.

· Precautionary statements

P210 Keep away from flames and hot surfaces. – No smoking.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Product safety department
- · Contact: Mr Eleazar dela Cruz
- · Date of preparation / last revision 01/16/2018 / 2
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TVL: Treshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3 Flam. Liq. 4: Flammable liquids – Category 4

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3