

Printing date 02/12/2018 Version 1 Reviewed on 02/12/2018

## 1 Identification

· Product identifier

· Product Description: Epoxy Curing Agent

Product code: Cardolite NX-8401

- Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Cardolite Corporation

11 Deer Park Drive, Suite 124 Monmouth Junction, NJ 08852

USA

Tel: (973) 344-5015 Regulatory@cardolite.com

- · Information department: Product safety department
- · Emergency telephone number: 24 Hour Emergency: 800-424-9300 CHEMTREC

## 2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Ethylenediamine

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

· Precautionary statements

Avoid contact with surface water.

(Contd. on page 2)



Printing date 02/12/2018 Version 1 Reviewed on 02/12/2018

**Product Description: Epoxy Curing Agent** 

(Contd. of page 1)

Incinerate contens/container in accordance with local / regional / national / international regulations.

Use chemical resistant Impervious gloves approved as per ASTM F739.

Remove content in container as much as possible. Rinse the container drum with water and recycle rinse water for next batch.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves / eye protection / face protection.
P284 [In case of inadequate ventilation] wear respiratory protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P342+P311 If experiencing respiratory symptoms: Call a poison center/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- NFPA ratings (scale 0 4)



Health = 1 Fire = 1 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 1 Fire = 1

Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

### · Dangerous Components:

107-15-3 Ethylenediamine

♦ Flam. Liq. 3, H226; ♦ Resp. Sens. 1, H334; ♦ Skin Corr. 1B, H314; ♦ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Sens. 1, H317

< 1.0%

### 4 First-aid measures

- Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)



Printing date 02/12/2018 Version 1 Reviewed on 02/12/2018

**Product Description: Epoxy Curing Agent** 

(Contd. of page 2)

 Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters

Promptly isolate the scene by removing all person from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

· Protective equipment: No special measures required.

### 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**Protective Action Criteria for Chemicals** 

· PAC-1:	
107-15-3 Ethylenediamine	0.88 ppm
· PAC-2:	
107-15-3 Ethylenediamine	9.7 ppm
· PAC-3:	
107-15-3 Ethylenediamine	20 ppm

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities

These products should be kept tightly sealed in their original containers when not in use, and stored in a cool, dry place that does not exceed 40 °C.

- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.



Printing date 02/12/2018 Version 1 Reviewed on 02/12/2018

**Product Description: Epoxy Curing Agent** 

(Contd. of page 3)

## 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- Control parameters
- · Components with limit values that require monitoring at the workplace:

#### 107-15-3 Ethylenediamine

PEL Long-term value: 25 mg/m³, 10 ppm REL Long-term value: 25 mg/m³, 10 ppm TLV Long-term value: 25 mg/m³, 10 ppm Skin

Additional information: The lists that were valid during the creation were used as basis.

#### · Exposure controls

Use local exhaust ventilation. Suitable respiratory equipment should be used in cases of insufficient ventilation.

#### · Personal protective equipment:

### · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

#### · Breathing equipment:

If exposure are expected, use of NIOSH-certified organic-vapor cartridge with a particulate pre-filter approved with assigned protection factor.

Wear NIOSH-certified respirator with assigned protection factor (AFP) of at least 50.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

### · Protection of hands:

Impervious aloves

Chemical resistant protective gloves



#### Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

(Contd. of page 4)



## Safety Data Sheet acc. to OSHA HCS

Printing date 02/12/2018 Version 1 Reviewed on 02/12/2018

**Product Description: Epoxy Curing Agent** 

· Eye protection:

Tightly sealed goggles

· Body protection: Protective work clothing

## 9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid Whitish
Odor: Amine-like
Odor threshold: Not determined.

• **pH-value at 25 °C (77 °F):** 10.5

· Change in condition

Melting point/Melting range: Undetermined. Boiling point/Boiling range: Undetermined.

• Flash point: >100 °C (>212 °F)

· Flammability (solid, gaseous): Not applicable.

• **Decomposition temperature:** Not determined.

• **Auto igniting:** Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower:Not determined.Upper:Not determined.

· Vapor pressure: Not determined.

• **Density at 25 °C (77 °F):** 1.0388 g/cm³ (8.66879 lbs/gal)

Relative density
Vapor density
Evaporation rate
Not determined.
Not determined.
Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

· Solvent content:

Solids content: > 55% %

(Contd. on page 6)



Printing date 02/12/2018 Version 1 Reviewed on 02/12/2018

**Product Description: Epoxy Curing Agent** 

(Contd. of page 5)

· Other information

No further relevant information available.

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Product is stable.
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- LD/LC50 values that are relevant for classification:

Irritating to eyes and skin.

#### 107-15-3 Ethylenediamine

Oral	LD50	866 mg/kg (rat)
Dermal	LD50	560 mg/kg (rabbit)
Inhalative	LC50/4 h	14.7 mg/l (rat)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.

(Contd. on page 7)



Printing date 02/12/2018 Version 1 Reviewed on 02/12/2018

**Product Description: Epoxy Curing Agent** 

(Contd. of page 6)

- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow product to reach surfcace water, ground water, water course or sewage system.

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

Transport information	
· UN-Number · DOT, ADR, ADN, IMDG, IATA	Non-hazardous for transport
· UN proper shipping name · DOT, ADR, ADN, IMDG, IATA	Non-hazardous for transport
· Transport hazard class(es)	
· DOT, ADN, IMDG, IATA · Class	Non-hazardous for transport
· ADR · Class	Non-hazardous for transport Miscellaneous dangerous substances and articles
· Packing group · DOT, ADR, IMDG, IATA	Non-hazardous for transport
· Environmental hazards:	Not applicable.
· Special precautions for user	Not applicable.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	of Not applicable.
· UN "Model Regulation":	Non-hazardous for transport



Printing date 02/12/2018 Version 1 Reviewed on 02/12/2018

**Product Description: Epoxy Curing Agent** 

(Contd. of page 7)

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara
- · Section 355 (extremely hazardous substances):

107-15-3 Ethylenediamine

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

Not all ingredients are listed.

107-15-3 Ethylenediamine

7732-18-5 water, distilled, conductivity or of similar purity

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

107-15-3 Ethylenediamine

D

· TLV (Threshold Limit Value established by ACGIH)

107-15-3 Ethylenediamine

Α4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Ethylenediamine

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

(Contd. on page 9)



Printing date 02/12/2018 Version 1 Reviewed on 02/12/2018

**Product Description: Epoxy Curing Agent** 

(Contd. of page 8)

Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray P261 P280 Wear protective gloves / eye protection / face protection. P284 [In case of inadequate ventilation] wear respiratory protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P342+P311 If experiencing respiratory symptoms: Call a poison center/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: Mr Eleazar dela Cruz
- Date of preparation / last revision 02/12/2018 / -
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TVL: Treshold Limit Value PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1