

1 Identification

- **Product identifier**
- **Product Description:**
Epoxy Curing Agent
Epoxy Curing Agent
- **Product code:** Cardolite NX-5050
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Cardolite Corporation
11 Deer Park Drive, Suite 124
Monmouth Junction, NJ 08852
USA
Tel: (973) 344-5015
Regulatory@cardolite.com
- **Information department:** Product safety department
- **Emergency telephone number:** 24 Hour Emergency: 800-424-9300 CHEMTREC

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS05 GHS07

- **Signal word** Danger

- **Hazard-determining components of labeling:**

m-Phenylenebis(methylamine)

(Contd. on page 2)

Printing date 03/15/2018

Version 4

Reviewed on 03/15/2018

Product Description: Epoxy Curing Agent

(Contd. of page 1)

Hazard statements

- H225 Highly flammable liquid and vapor.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H317 May cause an allergic skin reaction.

Precautionary statements

- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a poison center/doctor.
- P321 Specific treatment (see on this label).
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:
NFPA ratings (scale 0 - 4)

 Health = 2
 Fire = 3
 Reactivity = 0

HMIS-ratings (scale 0 - 4)

 Health = 2
 Fire = 3
 Reactivity = 0

Other hazards
Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients
Chemical characterization: Mixtures

- **Description:** Mixture of the substances listed below with nonhazardous additions.

Dangerous Components:

1330-20-7	Xylenes 	8.0 - 12.0%
67-63-0	Propan-2-ol 	5.0 - 8.0%
1477-55-0	m-Phenylenebis(methylamine) 	< 5.0%

4 First-aid measures
Description of first aid measures

- **General information:** Immediately remove any clothing soiled by the product.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/15/2018

Version 4

Reviewed on 03/15/2018

Product Description: Epoxy Curing Agent

(Contd. of page 2)

- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
Promptly isolate the scene by removing all person from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

1330-20-7	Xylenes	130 ppm
67-63-0	Propan-2-ol	400 ppm

- **PAC-2:**

1330-20-7	Xylenes	920* ppm
67-63-0	Propan-2-ol	2000* ppm

- **PAC-3:**

1330-20-7	Xylenes	2500* ppm
-----------	---------	-----------

(Contd. on page 4)

Product Description: Epoxy Curing Agent

67-63-0 Propan-2-ol

(Contd. of page 3)

12000** ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

1330-20-7 Xylenes

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

67-63-0 Propan-2-ol

PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI

(Contd. on page 5)

US

Printing date 03/15/2018

Version 4

Reviewed on 03/15/2018

Product Description: Epoxy Curing Agent

(Contd. of page 4)

 · **Ingredients with biological limit values:**
1330-20-7 Xylenes

BEI	1.5 g/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: Methylhippuric acids

67-63-0 Propan-2-ol

BEI	40 mg/L
	Medium: urine
	Time: end of shift at end of workweek
	Parameter: Acetone (background, nonspecific)

 · **Additional information:** The lists that were valid during the creation were used as basis.

 · **Exposure controls**

 · **Personal protective equipment:**

 · **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Avoid contact with the skin.
 Avoid contact with the eyes and skin.

 · **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

 · **Protection of hands:**


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

 · **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

 · **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

 · **Eye protection:**


Tightly sealed goggles

 · **Body protection:** Protective work clothing

US

(Contd. on page 6)

Product Description: Epoxy Curing Agent

(Contd. of page 5)

9 Physical and chemical properties

 · **Information on basic physical and chemical properties**

 · **General Information**

 · **Appearance:**

Form:	Liquid
Color:	Red-brown
Odor:	Amine-like
Odor threshold:	Not determined.

 · **pH-value at 25 °C (77 °F):** 10.5

 · **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	> 66 °C (>150.8 °F)

 · **Flash point:** 20 °C (68 °F)

 · **Flammability (solid, gaseous):** Not applicable.

 · **Decomposition temperature:** Not determined.

 · **Auto igniting:** Product is not selfigniting.

 · **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

 · **Explosion limits:**

Lower:	Not determined.
Upper:	Not determined.

 · **Vapor pressure:** Not determined.

 · **Density at 25 °C (77 °F):** 0.97778 g/cm³ (8.15957 lbs/gal)

 · **Relative density** Not determined.

 · **Vapor density** Not determined.

 · **Evaporation rate** Not determined.

 · **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

 · **Partition coefficient (n-octanol/water):** Not determined.

 · **Viscosity:**

Dynamic at 25 °C (77 °F):	1000 cps
Kinematic:	Not determined.

 · **Solvent content:**

Solids content: ~ 80.0 %

 · **Other information** No further relevant information available.

10 Stability and reactivity

 · **Reactivity** No further relevant information available.

 · **Chemical stability**

 · **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

 · **Possibility of hazardous reactions** No dangerous reactions known.

(Contd. on page 7)

Product Description: Epoxy Curing Agent

(Contd. of page 6)

- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**
Irritating to eyes and skin.

1330-20-7 Xylenes

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

67-63-0 Propan-2-ol

Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

1477-55-0 m-Phenylenebis(methylamine)

Oral	LD50	1,040 mg/kg (rat)
Inhalative	LC50/4 h	2.4 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	Xylenes	3
67-63-0	Propan-2-ol	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 8)

Product Description: Epoxy Curing Agent



(Contd. of page 7)

- **Additional ecological information:**
- **General notes:**
 Water hazard class 2 (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Must not reach bodies of water or drainage ditch undiluted or unneutralized.
 Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information


- | | |
|-------------------------------------|---|
| · UN-Number | UN1866 |
| · DOT, ADR, IMDG, IATA | UN1866 |
| · UN proper shipping name | Resin solution |
| · DOT | Resin solution |
| · ADR | 1866 Resin solution |
| · IMDG, IATA | RESIN SOLUTION |
| · Transport hazard class(es) | |
| · DOT | |
| |  |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · ADR | |
| |  |
| · Class | 3 Flammable liquids
Miscellaneous dangerous substances and articles |

(Contd. on page 9)

US

Product Description: Epoxy Curing Agent

(Contd. of page 8)

· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E,S-E
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	
	Not applicable.
· Transport/Additional information:	
· ADR	
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN1866, Resin solution, 3, II

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

1330-20-7 Xylenes

67-63-0 Propan-2-ol

TSCA (Toxic Substances Control Act):

Substance is listed and covered by Significant New Use Rule at U.S. 40 CFR 721.10058

All ingredients are listed.

(Contd. on page 10)

US

Product Description: Epoxy Curing Agent

(Contd. of page 9)

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

1330-20-7	Xylenes	I
-----------	---------	---

- **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	Xylenes	A4
67-63-0	Propan-2-ol	A4

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS05 GHS07

- **Signal word** Danger

- **Hazard-determining components of labeling:**

m-Phenylenebis(methylamine)

- **Hazard statements**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

- **Precautionary statements**

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

US

(Contd. on page 11)

Product Description: Epoxy Curing Agent

(Contd. of page 10)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Product safety department
- **Contact:** Mr Eleazar dela Cruz
- **Date of preparation / last revision** 03/15/2018 / 3
- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TVL: Treshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEL: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3