

Printing date 04/12/2018 Version 2 Reviewed on 04/12/2018

1 Identification

- · Product identifier
- · Product Description: Epoxy Curing Agent
- · Product code: Cardolite NX-2003D
- Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
 Cardolite Corporation
 11 Deer Park Drive, Suite 124
 Monmouth Junction, NJ 08852
 USA

Tel: (973) 344-5015 Regulatory@cardolite.com

- · Information department: Product safety department
- · Emergency telephone number: 24 Hour Emergency: 800-424-9300 CHEMTREC

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Muta. 2 H341 Suspected of causing genetic defects.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS05 Corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS05 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

2,2'-Iminodiethylamine Ethylenediamine

(Contd. on page 2)



Printing date 04/12/2018 Version 2 Reviewed on 04/12/2018

Product Description: Epoxy Curing Agent

(Contd. of page 1)

Phenol

· Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor. Specific treatment (see on this label). P321

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *1 Fire = 1Reactivity = 0

- Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangero	us Components:	
111-40-0	2,2'-Iminodiethylamine Acute Tox. 2, H330; Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; STOT SE 3, H335	5.0 - 9.0%
107-15-3	Ethylenediamine Flam. Liq. 3, H226; Resp. Sens. 1, H334; Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Sens. 1, H317	< 1.0%
108-95-2	Phenol ♦ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; ♦ Muta. 2, H341; STOT RE 2, H373; ♦ Skin Corr. 1B, H314	< 1.0%



Printing date 04/12/2018 Version 2 Reviewed on 04/12/2018

Product Description: Epoxy Curing Agent

(Contd. of page 2)

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters

Promptly isolate the scene by removing all person from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

· Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:		
107-15-3	Ethylenediamine	0.88 ppm
108-95-2	Phenol	15 ppm
PAC-2:		
107-15-3	Ethylenediamine	9.7 ppm
108-95-2	Phenol	23 ppm
(Contd. on		(Contd. on page



Printing date 04/12/2018 Version 2 Reviewed on 04/12/2018

Product Description: Epoxy Curing Agent

		(Contd. of page 3)
· PAC-3:		
107-15-3	Ethylenediamine	20 ppm
108-95-2	Phenol	200 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about protection against explosions and fires: No special measures required.
- Conditions for safe storage, including any incompatibilities

 Keep container tightly closed and in a well ventilated place.
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

107-1	5-3 Ethylenediamine						
PEL	Long-term value: 25 mg/m ³ , 10 ppm						
REL	Long-term value: 25 mg/m³, 10 ppm						
TLV	Long-term value: 25 mg/m³, 10 ppm Skin						
108-9	95-2 Phenol						
PEL	ong-term value: 19 mg/m³, 5 ppm Skin						
REL	REL Long-term value: 19 mg/m³, 5 ppm Ceiling limit value: 60* mg/m³, 15.6* ppm *15-min; Skin						
TLV	Long-term value: 19 mg/m³, 5 ppm Skin; BEI						

· Ingredients with biological limit values:

108-95-2 Phenol

BEI 250 mg/g creatinine Medium: urine

Time: end of shift

Parameter: Phenol with hydrolysis (background, nonspecific)

· Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)



Printing date 04/12/2018 Version 2 Reviewed on 04/12/2018

Product Description: Epoxy Curing Agent

(Contd. of page 4)

· Exposure controls

Use local exhaust ventilation. Suitable respiratory equipment should be used in cases of insufficient ventilation.

· Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

- Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Color: Red-brown
Odor: Amine-like
Odor threshold: Not determined.

· pH-value: Not determined.

(Contd. on page 6)



Printing date 04/12/2018 Version 2 Reviewed on 04/12/2018

Product Description: Epoxy Curing Agent

	(Contd. of page
Change in condition Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	> 66 °C (>150.8 °F)
· Flash point:	104 ℃ (219.2 °F)
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapor pressure:	Not determined.
 Density at 25 °C (77 °F): Relative density Vapor density Evaporation rate 	0.99935 g/cm³ (8.33958 lbs/gal) Not determined. Not determined. Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/w	ater): Not determined.
· Viscosity: Dynamic at 25 °C (77 °F): Kinematic:	700 cps Not determined.
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability Product is stable.
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- LD/LC50 values that are relevant for classification:

Irritating to eyes and skin.

111-40-0	2,2'-lmino	diethylamine
Oral	LD50	1,080 mg/kg (rat)

(Contd. on page 7)



Printing date 04/12/2018 Version 2 Reviewed on 04/12/2018

Product Description: Epoxy Curing Agent

		(Contd. of page 6)
Dermal	LD50	1,090 mg/kg (rabbit)
Inhalative	LC50/4 h	0.3 mg/l (rat)
107-15-3 E	Ethylened	iamine
Oral	LD50	866 mg/kg (rat)
Dermal	LD50	560 mg/kg (rabbit)
Inhalative	LC50/4 h	14.7 mg/l (rat)
108-95-2 F	Phenol	
Oral	LD50	317 mg/kg (rat)
Dermal	LD50	850 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
108-95-2 Phenol	3
· NTP (National Toxicology Program)	
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 8)



Printing date 04/12/2018 Version 2 Reviewed on 04/12/2018

Product Description: Epoxy Curing Agent

· Other adverse effects No further relevant information available.

(Contd. of page 7)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

Transport information	
· UN-Number · DOT, ADR, ADN, IMDG, IATA	Non-hazardous for transport
· UN proper shipping name · DOT, ADR, ADN, IMDG, IATA	Not regulated as dangerous goods. Non-hazardous for transport
· Transport hazard class(es)	
· DOT, IMDG, IATA · Class · Label	Non-hazardous for transport
· ADR · Class	Non-hazardous for transport Miscellaneous dangerous substances and articles
· Label · ADN/R Class:	- Non-hazardous for transport
· Packing group · DOT, ADR, IMDG, IATA	Non-hazardous for transport
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user	Not applicable.
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	x II of Not applicable.
· UN "Model Regulation":	Non-hazardous for transport

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section	355 (extre	mel	y hazardous substances):
40-4-0				

107-15-3 Ethylenediamine

108-95-2 Phenol



Printing date 04/12/2018 Version 2 Reviewed on 04/12/2018

Product Description: Epoxy Curing Agent

	(Contd. of page
Section 313 (Specific toxic chemical listings):	
108-95-2 Phenol	
TSCA (Toxic Substances Control Act):	
68413-29-6 Alkylated Phenolic Polyamine	
107-15-3 Ethylenediamine	
108-95-2 Phenol	
TSCA new (21st Century Act) (Substances not listed)	
111-40-0 2,2'-Iminodiethylamine	
Proposition 65	
Chemicals known to cause cancer:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
Carcinogenic categories	
EPA (Environmental Protection Agency)	
107-15-3 Ethylenediamine	D
108-95-2 Phenol	D
TLV (Threshold Limit Value established by ACGIH)	'
107-15-3 Ethylenediamine	
108-95-2 Phenol	A

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





None of the ingredients is listed.

GHS05 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

2,2'-Iminodiethylamine

Ethylenediamine

Phenol

· Hazard statements

H315 Causes skin irritation.

H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.



Printing date 04/12/2018 Version 2 Reviewed on 04/12/2018

Product Description: Epoxy Curing Agent

(Contd. of page 9)

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor. P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Product safety department
- Contact: Mr Eleazar dela Cruz
- Date of preparation / last revision 04/12/2018 / 1
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TVL: Treshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEL: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Muta. 2: Germ cell mutagenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2