

Printing date 01/14/2019

Version 1

Reviewed on 01/14/2019

1 Identification

- **Product identifier**
- **Product Description: Phenalkamine Adduct**
- **Product code:** LITE 5262
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Cardolite Corporation
140 Wharton Road
Bristol, PA 19007
United States
Tel: 1-800-322-7365
Regulatory@cardolite.com
- **Information department:** Product safety department
- **Emergency telephone number:** 24 Hour Emergency: 800-424-9300 CHEMTREC

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

Flam. Liq. 4 H227 Combustible liquid.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05



GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**
1,3-Cyclohexanedimethanamine
3-Aminopropylidimethylamine
Butanol

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/14/2019

Version 1

Reviewed on 01/14/2019

Product Description: Phenalkamine Adduct

(Contd. of page 1)

Ethylenediamine

- **Hazard statements**

H227 Combustible liquid.

H314 Causes severe skin burns and eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

- **Precautionary statements**

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 3

Fire = 2

Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = *3

Fire = 2

Reactivity = 0

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous Components:**

2579-20-6	1,3-Cyclohexanedimethanamine ⚠ Skin Corr. 1A, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312	<15.0%
109-55-7	3-Aminopropyldimethylamine ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 3, H311; ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317	<10.0%
71-36-3	Butanol ⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	<5.0%
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2A, H319	<2.0%
107-15-3	Ethylenediamine ⚠ Flam. Liq. 3, H226; ⚠ Resp. Sens. 1, H334; ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Sens. 1, H317	<1.0%

US

(Contd. on page 3)

Product Description: Phenalkamine Adduct

(Contd. of page 2)

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
Promptly isolate the scene by removing all person from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Prevent seepage into sewage system, workpits and cellars.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

109-55-7	3-Aminopropyldimethylamine	1.2 ppm
71-36-3	Butanol	60 ppm
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	6.5 mg/m ³

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/14/2019

Version 1

Reviewed on 01/14/2019

Product Description: Phenalkamine Adduct

(Contd. of page 3)

107-15-3	Ethylenediamine	0.88 ppm
• PAC-2:		
109-55-7	3-Aminopropyldimethylamine	13 ppm
71-36-3	Butanol	800 ppm
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	72 mg/m ³
107-15-3	Ethylenediamine	9.7 ppm
• PAC-3:		
109-55-7	3-Aminopropyldimethylamine	89 ppm
71-36-3	Butanol	8000** ppm
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol	430 mg/m ³
107-15-3	Ethylenediamine	20 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

107-15-3 Ethylenediamine

PEL	Long-term value: 25 mg/m ³ , 10 ppm
REL	Long-term value: 25 mg/m ³ , 10 ppm
TLV	Long-term value: 25 mg/m ³ , 10 ppm
	Skin

71-36-3 Butanol

PEL	Long-term value: 300 mg/m ³ , 100 ppm
REL	Ceiling limit value: 150 mg/m ³ , 50 ppm
	Skin

(Contd. on page 5)

Product Description: Phenalkamine Adduct

(Contd. of page 4)

 TLV Long-term value: 61 mg/m³, 20 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing.
 - Wash hands before breaks and at the end of work.
 - Avoid contact with the eyes.
 - Avoid contact with the eyes and skin.
- **Breathing equipment:**
 - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 - The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
 - Form:** Liquid
 - Color:** Yellow-brown
- **Odor:** Amine-like
- **Odor threshold:** Not determined.
- **pH-value:** Not determined.

(Contd. on page 6)

Safety Data Sheet
 acc. to OSHA HCS

Printing date 01/14/2019

Version 1

Reviewed on 01/14/2019

Product Description: Phenalkamine Adduct

(Contd. of page 5)

· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. Undetermined.
· Flash point:	77 °C (170.6 °F)
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapor pressure:	Not determined.
· Density at 25 °C (77 °F): · Relative density · Vapor density · Evaporation rate	0.99096 g/cm ³ (8.26956 lbs/gal) Not determined. Not determined. Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity: Dynamic at 25 °C (77 °F): Kinematic:	2500 - 3200 cps Not determined.
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Product is stable.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**
Irritating to eyes and skin.

(Contd. on page 7)

US

Product Description: Phenalkamine Adduct

(Contd. of page 6)

2579-20-6 1,3-Cyclohexanedimethanamine		
Oral	LD50	700 mg/kg (rat)
Dermal	LD50	1,700 mg/kg (rabbit)
109-55-7 3-Aminopropyldimethylamine		
Oral	LD50	1,870 mg/kg (rat)
Dermal	LD50	490 mg/kg (rabbit)
107-15-3 Ethylenediamine		
Oral	LD50	866 mg/kg (rat)
Dermal	LD50	560 mg/kg (rabbit)
Inhalative	LC50/4 h	14.7 mg/l (rat)
71-36-3 Butanol		
Oral	LD50	790 mg/kg (rat)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4 h	8,000 mg/l (rat)
90-72-2 2,4,6-Tris(Dimethylaminomethyl)Phenol		
Oral	LD50	2,169 mg/kg (rat)
Dermal	LD50	1,260 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Strong caustic effect on skin and mucous membranes.
- **on the eye:**
Strong caustic effect.
Strong irritant with the danger of severe eye injury.
- **Sensitization:**
Sensitization possible through inhalation.
Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Corrosive
Irritant
Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 8)

Safety Data Sheet
 acc. to OSHA HCS

Printing date 01/14/2019

Version 1

Reviewed on 01/14/2019

Product Description: Phenalkamine Adduct



(Contd. of page 7)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---|
| <ul style="list-style-type: none"> · UN-Number · DOT, ADR, IMDG, IATA | UN2735 |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · ADR · IMDG, IATA | Amines, liquid, corrosive, n.o.s. (Ethylenediamine)
2735 Amines, liquid, corrosive, n.o.s. (Ethylenediamine)
AMINES, LIQUID, CORROSIVE, N.O.S.
(ETHYLENEDIAMINE) |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT, IMDG, IATA |  |
| <ul style="list-style-type: none"> · Class · Label | 8 Corrosive substances
8 |
| <ul style="list-style-type: none"> · ADR |  |
| <ul style="list-style-type: none"> · Class · Label | 8 Corrosive substances
Miscellaneous dangerous substances and articles
8 |

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/14/2019

Version 1

Reviewed on 01/14/2019

Product Description: Phenalkamine Adduct

(Contd. of page 8)

<ul style="list-style-type: none"> • Packing group • DOT, ADR, IMDG, IATA 	III
• Environmental hazards:	Not applicable.
<ul style="list-style-type: none"> • Special precautions for user • Danger code (Kemler): • EMS Number: 	Warning: Corrosive substances 80 F-A,S-B
• Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
• Transport/Additional information:	
<ul style="list-style-type: none"> • DOT • Quantity limitations 	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
<ul style="list-style-type: none"> • ADR • Excepted quantities (EQ) 	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<ul style="list-style-type: none"> • IMDG • Limited quantities (LQ) • Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
• UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (ETHYLENEDIAMINE), 8, III

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

107-15-3	Ethylenediamine
----------	-----------------

- **Section 313 (Specific toxic chemical listings):**

71-36-3	Butanol
---------	---------

- **TSCA (Toxic Substances Control Act):**

2579-20-6	1,3-Cyclohexanedimethanamine
109-55-7	3-Aminopropyldimethylamine
71-36-3	Butanol
90-72-2	2,4,6-Tris(Dimethylaminomethyl)Phenol
107-15-3	Ethylenediamine

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

(Contd. on page 10)

US

Safety Data Sheet
 acc. to OSHA HCS

Printing date 01/14/2019

Version 1

Reviewed on 01/14/2019

Product Description: Phenalkamine Adduct

(Contd. of page 9)

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Carcinogenic categories
EPA (Environmental Protection Agency)

71-36-3 Butanol

D

107-15-3 Ethylenediamine

D

TLV (Threshold Limit Value established by ACGIH)

107-15-3 Ethylenediamine

A4

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms


GHS05 GHS08

Signal word Danger

Hazard-determining components of labeling:

1,3-Cyclohexanedimethanamine

3-Aminopropyldimethylamine

Butanol

Ethylenediamine

Hazard statements

H227 Combustible liquid.

H314 Causes severe skin burns and eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

Precautionary statements

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

US

(Contd. on page 11)

Product Description: Phenalkamine Adduct

(Contd. of page 10)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Product safety department
- **Contact:** Mr Eleazar dela Cruz
- **Date of preparation / last revision** 01/14/2019 / -
- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TVL: Treshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Liq. 4: Flammable liquids – Category 4

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3