

# Cardolite<sup>®</sup> NX-5454

## Epoxy Curing Agent

### Technical Datasheet

#### DESCRIPTION

Cardolite NX-5454 is a low viscosity, solvent and benzyl alcohol free phenalkamine curing agent designed for epoxy coating applications protecting metal and concrete substrates. It has excellent rapid cure properties, even at low temperatures, offers very good chemical resistance, and provides excellent adhesion on wet or otherwise unprepared surfaces and green concrete. Industrial, protective, and floor coatings can benefit from this product's excellent water resistance and corrosion protection.

#### PROPERTIES

PROPERTY	SPECIFICATION	TEST METHOD
Color (Gardner)	≤ 14	ASTM D1544
Viscosity @ 25°C (cPs)	700 - 1,200	ASTM D2196
Amine Value (mg KOH/g)	270 - 310	ASTM D2074
Volatile Loss (% weight)	≤ 3	ASTM D2369-98

PROPERTY	TYPICAL VALUE	TEST METHOD
Appearance	Yellow liquid	Visual
Theoretical Active Hydrogen Equivalent (AHEW) <sup>1</sup>	133	Calculated
Density @ 25°C (kg/L) (lbs/gal)	0.99 8.26	ASTM D1475
Flash point	101°C / 214°F	ASTM D93
Recommended Use Level (phr, EEW 190)	70	-
Shelf Life (Months)	6	-

Typical properties are not to be construed as specifications

<sup>1</sup> Based on total product weight

#### APPLICATIONS

Cardolite NX-5454 is usable in high solids or solvent free surface tolerant marine, industrial maintenance, protective, and floor coatings. Good chemical and water resistance make this curing agent especially acceptable for concrete or metal tank linings and pipe coatings. It can be used for coating applications under cold and humid conditions, even over damp and poorly prepared surfaces, and offers excellent film appearance at extreme conditions. This product's fast cure and good hardness make it ideal for applications requiring fast return to service. Its ability to cure over a wide temperature range and non-critical mix ratio can bring coatings broad application latitude.

#### ADVANTAGES

- Excellent combination of rapid cure and long pot-life at both ambient and low (<5°C/40°F) temperatures
- Continues to chemically crosslink at very low temperatures (<0°C/32°F)
- Excellent film quality even at low temperatures and high humidity
- Good adhesion to poorly prepared surfaces and green concrete
- Moisture tolerant during cure
- Excellent early water resistance
- Very good chemical resistance
- Good flexibility
- Compatible with most epoxy resins, solvents and their blends
- Superior corrosion resistance mitigating the need for anti-corrosion pigments
- Non-critical mix ratio
- No induction time required
- Solvent and benzyl alcohol free
- Based from natural, renewable, non-food chain raw material feedstock

## CURE PROPERTIES

	FORMULATION	TEST METHOD
Liquid Epoxy Resin (pbw, EEW 190)	100	
Cardolite NX-5454 (pbw)	70	
Mix viscosity @ 25°C (cPs)	4,300	
Gel time, 50 g @ 25°C (min)	18	NTM-15
Thin film dry times, 8 mils (200 micron)		
@ 25°C (77°F) (hrs hard/through)	2 / 4	ASTM D5895
@ 5°C (41°F) (hrs hard/through)	7.5 / 11	ASTM D5895
@ 0°C (32°F) (hrs hard/through)	10 / 16	ASTM D5895
Film appearance @ 10°C, 92% RH	Clear	Visual

## REGULATORY STATUS

Please refer to the material safety data sheet (MSDS). Specific information regarding chemical inventory listing can be obtained from your local sales representative.

## SAFETY PRECAUTIONS

Please refer to the material safety data sheet (MSDS). Copies of the MSDS can be requested on the Cardolite website or via your local sales representative.

## STABILITY AND STORAGE

Cardolite products may absorb moisture and carbon dioxide when left in open containers, which could result in increased viscosity, discoloration, reduction of reactivity, and/or crystallization of the products. These products should be kept tightly sealed in their original containers when not in use, and stored in a cool, dry place.

## CONTACT INFORMATION



<http://www.cardolite.com>

Cardolite Corporation  
140 Wharton Road  
Bristol, PA 19007  
United States of America

Cardolite Specialty  
Chemicals Europe NV  
Wijmenstraat 21K / 2  
B-9030 Mariakerke (Gent)  
Belgium

Cardolite Specialty Chemicals  
India LLP  
Plot No. IP-1 & IP-2, Mangalore  
Special Economic Zone  
Bajpe, Mangalore 574 142  
India

Cardolite Chemical  
Zhuhai Ltd.  
1248 Ninth Shihua Road  
Gaolan Port Economic Zone  
Zhuhai, Guangdong 519050  
P.R. China

T: +1-800-322-7365

T: +32 (0) 92658826

T: + 91 (0) 824 2888 300

T: +86-756-726-9066

## DISCLAIMER & COPYRIGHT

All statements, technical information and recommendations contained herein are based on tests Cardolite believes to be reliable, but the accuracy or completeness thereof is not guaranteed. Actual test method procedures may differ from listed standards; major differences are noted. Limitation of liability and remedy: Purchase or use of these products constitutes an agreement with seller and manufacturer that, if the product proves to be defective or unsuitable, seller's and manufacturer's liability and the exclusive remedy, regardless of tort or contract theory or of incidental or consequential damages shall be to receive, at seller's or manufacturer's option, an equivalent quantity of replacement product or a refund of the purchase price. This datasheet is copyrighted to Cardolite Corporation and may be reproduced but not altered in any way.